

DIN EN ISO 583:2023-06 (E)

Conveyor belts with a textile carcass - Total belt thickness and thickness of constitutive elements - Test methods (ISO 583:2023)

Contents		Page
European foreword.....		3
Foreword.....		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	Determination of total belt thickness	5
4.1	Apparatus.....	5
4.2	Test piece.....	5
4.3	Measurement points.....	6
4.4	Procedure.....	7
4.5	Expression of results.....	7
5	Determination of thickness of covers	7
5.1	General.....	7
5.2	Method used when covers can be removed completely from carcass.....	7
5.2.1	Principle.....	7
5.2.2	Apparatus.....	7
5.2.3	Test piece.....	7
5.2.4	Measurement points.....	7
5.2.5	Procedure.....	7
5.2.6	Expression of results.....	8
5.3	Method used when covers cannot be removed completely from carcass.....	9
5.3.1	Principle.....	9
5.3.2	Apparatus.....	9
5.3.3	Test piece.....	9
5.3.4	Measurement points.....	9
5.3.5	Procedure.....	9
5.3.6	Expression of results.....	10
6	Determination of carcass thickness	10
6.1	Carcass thickness without covers.....	10
6.2	Carcass thickness with covers.....	10
6.3	Expression of results.....	10
7	Determination of thickness of interlayer	11
7.1	General.....	11
7.2	Method used when elastomeric material in interlayer can be removed completely from adjacent fabric ply.....	11
7.2.1	Principle.....	11
7.2.2	Apparatus.....	11
7.2.3	Test piece.....	11
7.2.4	Measurement points.....	11
7.2.5	Procedure.....	11
7.2.6	Expression of results.....	11
7.3	Method for use when elastomeric material in interlayer cannot be separated completely from adjacent fabric ply.....	12
7.3.1	Principle.....	12
7.3.2	Apparatus.....	12
7.3.3	Test piece.....	12

7.3.4	Measurement points	12
7.3.5	Procedure	12
7.3.6	Expression of results	12
8	Test report	12
	Bibliography	14