ISO 8066-4:2023-07 (E)

Rubber and plastics hoses and hose assemblies for automotive air conditioning - Specification - Part 4: Low vibration transmission type for Refrigerant 1234yf

Contents

Page

Foreword v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Classification 2
4.1 Construction and material 2
4.2 Pressure class 2
4.3 Moisture-ingression grades 2

5 Dimensions 2
5.1 Hose inside diameters 2
5.2 Hose wall thickness variation 3

6 Testing and performance requirements 3
6.1 Test conditions 3
6.2 Gas leakage 3
6.2.1 Method A for type test and production test 3
6.2.2 Procedure for method A 3
6.2.3 Method B for routine test 3
6.2.4 Procedure for method B 4
6.3 Refrigerant permeation 4
6.3.1 Requirement 4
6.3.2 Procedure 4
6.4 Ageing 4
6.4.1 Requirement 4
6.4.2 Procedure 4
6.5 Low-temperature test 4
6.6 Vacuum resistance 4
6.6.1 General 4
6.6.2 Requirement 4
6.6.3 Procedure 5
6.7 Length change under pressure 5
6.7.1 Requirement 5
6.7.2 Procedure 5
6.8 Minimum bursting pressure 5
6.9 Proof pressure 5
6.10 Extraction by R1234yf 6
6.11 Ozone resistance 6
6.12 Hose cleanliness 6
6.12.1 Requirement 6
6.12.2 Procedure 6
6.13 Impulse test 6
6.13.1 Requirement 6
6.13.2 Procedure 6
6.14 Moisture ingression 7
6.15 Coupling integrity (sealability) 7
6.16 Vibration transmissibility 7

7 Frequency of testing 7
8 Marking 8
9 Test report 8
10 Recommendations for packaging and storage 8
Annex A (normative) Determination of refrigerant permeation 9
Annex B (normative) Low-temperature test 12
Annex C (normative) Determination of amount of matter extracted from hoses by liquid R1234yf 13
Annex D (normative) Impulse test 14
Annex E (normative) Moisture ingression test 18
Annex F (normative) Coupling integrity (sealability) 22
Annex G (normative) Vibration transmissibility 24
Annex H (normative) Test frequency 27
Annex I (informative) Production tests 28
Bibliography 29