

ISO 8066-4:2023-07 (E)

Rubber and plastics hoses and hose assemblies for automotive air conditioning - Specification - Part 4: Low vibration transmission type for Refrigerant 1234yf

Contents	Page
Foreword	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Classification	2
4.1 Construction and material	2
4.2 Pressure class	2
4.3 Moisture-ingression grades	2
5 Dimensions	2
5.1 Hose inside diameters	2
5.2 Hose wall thickness variation	3
6 Testing and performance requirements	3
6.1 Test conditions	3
6.2 Gas leakage	3
6.2.1 Method A for type test and production test	3
6.2.2 Procedure for method A	3
6.2.3 Method B for routine test	3
6.2.4 Procedure for method B	4
6.3 Refrigerant permeation	4
6.3.1 Requirement	4
6.3.2 Procedure	4
6.4 Ageing	4
6.4.1 Requirement	4
6.4.2 Procedure	4
6.5 Low-temperature test	4
6.6 Vacuum resistance	4
6.6.1 General	4
6.6.2 Requirement	4
6.6.3 Procedure	5
6.7 Length change under pressure	5
6.7.1 Requirement	5
6.7.2 Procedure	5
6.8 Minimum bursting pressure	5
6.9 Proof pressure	5
6.10 Extraction by R1234yf	6
6.11 Ozone resistance	6
6.12 Hose cleanliness	6
6.12.1 Requirement	6
6.12.2 Procedure	6
6.13 Impulse test	6
6.13.1 Requirement	6
6.13.2 Procedure	6
6.14 Moisture ingression	7
6.15 Coupling integrity (sealability)	7
6.16 Vibration transmissibility	7

7	Frequency of testing	7
8	Marking	8
9	Test report	8
10	Recommendations for packaging and storage	8
	Annex A (normative) Determination of refrigerant permeation	9
	Annex B (normative) Low-temperature test	12
	Annex C (normative) Determination of amount of matter extracted from hoses by liquid R1234yf	13
	Annex D (normative) Impulse test	14
	Annex E (normative) Moisture ingress test	18
	Annex F (normative) Coupling integrity (sealability)	22
	Annex G (normative) Vibration transmissibility	24
	Annex H (normative) Test frequency	27
	Annex I (informative) Production tests	28
	Bibliography	29