

# ISO 11424:2023-07 (E)

## Rubber hoses and tubing for air and vacuum systems for internal-combustion engines - Specification

---

| <b>Contents</b>   |  | <b>Page</b> |
|---|--|-------------|
| Foreword .....  |  | iv          |
| <b>1</b>  | <b>Scope .....</b>   | <b>1</b>    |
| <b>2</b>  | <b>Normative references .....</b>                          | <b>1</b>    |
| <b>3</b>  | <b>Terms and definitions .....</b>                         | <b>2</b>    |
| <b>4</b>  | <b>Classification .....</b>                                | <b>2</b>    |
| <b>4.1</b>  | <b>Types .....</b>   | <b>2</b>    |
| <b>4.2</b>  | <b>Classes .....</b>                                       | <b>2</b>    |
| <b>5</b>  | <b>Hose and tubing bores .....</b>                         | <b>3</b>    |
| <b>6</b>  | <b>Dimensions and tolerances .....</b>                     | <b>3</b>    |
| <b>6.1</b>  | <b>Hoses .....</b>   | <b>3</b>    |
| <b>6.2</b>  | <b>Tubing .....</b>  | <b>3</b>    |
| <b>7</b>  | <b>Requirements for physical properties .....</b>          | <b>4</b>    |
| <b>7.1</b>  | <b>Rubber compounds .....</b>                              | <b>4</b>    |
| <b>7.1.1</b>  | <b>Selection of test pieces .....</b>                      | <b>4</b>    |
| <b>7.1.2</b>  | <b>Hardness .....</b>                                      | <b>4</b>    |
| <b>7.1.3</b>  | <b>Tensile strength and elongation at break .....</b>      | <b>4</b>    |
| <b>7.1.4</b>  | <b>Change in properties after heat-ageing .....</b>        | <b>4</b>    |
| <b>7.1.5</b>  | <b>Compression set .....</b>                               | <b>5</b>    |
| <b>7.1.6</b>  | <b>Resistance to oxygenated fuels .....</b>                | <b>5</b>    |
| <b>7.1.7</b>  | <b>Resistance to oil no. 3 .....</b>                       | <b>5</b>    |
| <b>7.2</b>  | <b>Hose and tubing .....</b>                               | <b>5</b>    |
| <b>7.2.1</b>  | <b>Proof pressure .....</b>                                | <b>5</b>    |
| <b>7.2.2</b>  | <b>Minimum burst pressure .....</b>                        | <b>6</b>    |
| <b>7.2.3</b>  | <b>Adhesion .....</b>                                      | <b>6</b>    |
| <b>7.2.4</b>  | <b>Ozone resistance .....</b>                              | <b>6</b>    |
| <b>7.2.5</b>  | <b>Low-temperature flexibility after heat-ageing .....</b> | <b>6</b>    |
| <b>7.2.6</b>  | <b>Amount of extractable products .....</b>                | <b>6</b>    |
| <b>7.2.7</b>  | <b>Tear resistance .....</b>                               | <b>6</b>    |
| <b>7.2.8</b>  | <b>Vacuum resistance (only for Type A) .....</b>           | <b>6</b>    |
| <b>7.2.9</b>  | <b>Resistance to kinking .....</b>                         | <b>7</b>    |
| <b>7.3</b>  | <b>Requirement for all classes .....</b>                   | <b>7</b>    |
| <b>8</b>  | <b>Frequency of testing .....</b>                          | <b>8</b>    |
| <b>9</b>  | <b>Marking .....</b>                                       | <b>9</b>    |
| <b>10</b>   | <b>Recommendations for packaging and storage .....</b>     | <b>9</b>    |
| <b>Annex A (normative) Type and routine tests .....</b>         |  | <b>10</b>   |
| <b>Annex B (informative) Recommended production tests .....</b> |  | <b>11</b>   |
| <b>Bibliography .....</b>                                       |  | <b>12</b>   |