

DIN 7863-4:2023-10 (E)

Elastomer glazing and panel gaskets for windows and claddings - Material requirements - Part 4: PVC-P glazing and panel gaskets

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms and definitions | 5 |
| 4 | Classification | 5 |
| 4.1 | General | 5 |
| 4.2 | Temperature classes | 5 |
| 4.3 | Application classes | 5 |
| 5 | Requirements | 5 |
| 5.1 | Material requirements | 5 |
| 5.2 | Compatibility with adjacent materials | 6 |
| 6 | Shape and dimensions of gaskets | 6 |
| 7 | Test method | 7 |
| 7.1 | General | 7 |
| 7.2 | Hardness | 7 |
| 7.3 | Tensile strength and elongation at break | 7 |
| 7.4 | Compression set at ambient or elevated temperatures | 7 |
| 7.5 | Compression set at low temperatures | 7 |
| 7.6 | Artificial ageing | 7 |
| 7.7 | Behaviour after ozone exposure | 7 |
| 7.8 | Compatibility with contact media | 8 |
| 7.9 | Reaction to fire | 8 |
| 8 | Test report | 8 |
| Bibliography | | 9 |
| Tables | Table 1 -- Requirements for PVC-P materials of temperature class -25 °C to +70 °C for gaskets in window applications | 6 |