

# ISO 4633:2023-08 (E)

## Rubber seals - Joint rings for water supply, drainage and sewerage pipelines - Specification for materials

---

<b>Contents</b>		<b>Page</b>
Foreword		iv
<b>1</b>	<b>Scope</b>	<b>1</b>
<b>2</b>	<b>Normative references</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions</b>	<b>2</b>
<b>4</b>	<b>Classification</b>	<b>2</b>
<b>5</b>	<b>Requirements</b>	<b>2</b>
5.1	General	2
5.2	Effect on water quality	2
5.3	Microbiological deterioration	3
5.4	Dimensional tolerances	3
5.5	Imperfections and defects	3
5.6	Hardness	3
5.7	Tensile strength and elongation at break	3
5.8	Compression set in air	3
5.8.1	General	3
5.8.2	Compression set at 23 °C and 70 °C	4
5.8.3	Low-temperature compression set at -10 °C	4
5.9	Accelerated ageing in air	4
5.10	Stress relaxation in compression	4
5.11	Volume change in water	4
5.12	Ozone resistance	5
5.13	Splices of prevulcanized profile ends	5
5.13.1	Spliced joints	5
5.13.2	Strength of spliced joints	5
5.14	Summary of physical property requirements	5
<b>6</b>	<b>Optional requirements</b>	<b>6</b>
6.1	Low temperature performance at -25 °C, (type L)	6
6.2	Volume change in oil, (type O)	6
6.3	Lifetime estimation, (type LT)	6
6.3.1	General	6
6.3.2	Method 1 by stress relaxation	7
6.3.3	Method 2 by compression set	7
6.4	Summary of optional property requirements	7
<b>7</b>	<b>Test pieces and test temperature</b>	<b>8</b>
7.1	Preparation of test pieces	8
7.2	Test temperature	8
<b>8</b>	<b>Quality assurance</b>	<b>8</b>
<b>9</b>	<b>Storage</b>	<b>8</b>
<b>10</b>	<b>Designation</b>	<b>8</b>
<b>11</b>	<b>Marking and labelling</b>	<b>9</b>
<b>Annex A</b> (normative)	<b>Determination of splice strength</b>	<b>10</b>
<b>Annex B</b> (informative)	<b>Quality assurance</b>	<b>11</b>
<b>Annex C</b> (informative)	<b>Guidance on storage of seals</b>	<b>12</b>
<b>Annex D</b> (informative)	<b>Remarks regarding the lifetime estimation in <a href="#">6.3</a></b>	<b>13</b>
<b>Bibliography</b>		<b>14</b>