

Rubber seals - Joint rings for water supply, drainage and sewerage pipelines - Specification for materials

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Classification	2
5 Requirements	2
5.1 General	2
5.2 Effect on water quality	2
5.3 Microbiological deterioration	3
5.4 Dimensional tolerances	3
5.5 Imperfections and defects	3
5.6 Hardness	3
5.7 Tensile strength and elongation at break	3
5.8 Compression set in air	3
5.8.1 General	3
5.8.2 Compression set at 23 °C and 70 °C	4
5.8.3 Low-temperature compression set at -10 °C	4
5.9 Accelerated ageing in air	4
5.10 Stress relaxation in compression	4
5.11 Volume change in water	4
5.12 Ozone resistance	5
5.13 Splices of prevulcanized profile ends	5
5.13.1 Spliced joints	5
5.13.2 Strength of spliced joints	5
5.14 Summary of physical property requirements	5
6 Optional requirements	6
6.1 Low temperature performance at -25 °C, (type L)	6
6.2 Volume change in oil, (type O)	6
6.3 Lifetime estimation, (type LT)	6
6.3.1 General	6
6.3.2 Method 1 by stress relaxation	7
6.3.3 Method 2 by compression set	7
6.4 Summary of optional property requirements	7
7 Test pieces and test temperature	8
7.1 Preparation of test pieces	8
7.2 Test temperature	8
8 Quality assurance	8
9 Storage	8
10 Designation	8
11 Marking and labelling	9
Annex A (normative) Determination of splice strength	10
Annex B (informative) Quality assurance	11
Annex C (informative) Guidance on storage of seals	12
Annex D (informative) Remarks regarding the lifetime estimation in 6.3	13
Bibliography	14