

# ISO 24163-2:2024-01 (E)

## Clamp-in tyre valves for tyre pressure monitoring systems - Part 2: Test methods and performance

---

### Contents

	Page
<b>Foreword</b>	<b>iv</b>
<b>1 Scope</b>	<b>1</b>
<b>2 Normative references</b>	<b>1</b>
<b>3 Terms and definitions</b>	<b>1</b>
<b>4 Test fixture and valve hole dimensions</b>	<b>2</b>
<b>5 Test methods and performance requirements</b>	<b>3</b>
5.1 General	3
5.1.1 Appearance	3
5.1.2 Operating pressure	3
5.1.3 Installation procedure	3
5.1.4 Samples	3
5.2 Leakage test method	3
5.3 Valve core tests	5
5.3.1 Valve core specification for leakage tests	5
5.3.2 Valve core room temperature leakage test	5
5.3.3 Valve core low temperature leakage test	5
5.3.4 Valve core high temperature leakage test	5
5.3.5 Valve core over torque resistance test	6
5.3.6 Valve core endurance test	6
5.3.7 Valve core air flow rate test	7
5.4 Valve cap seal	7
5.4.1 Room temperature test (optional, for sealing caps only)	7
5.5 Valve to rim seal	8
5.5.1 Valve to rim seal leakage test — General	8
5.5.2 Valve to rim seal low temperature leakage test	8
5.5.3 Valve to rim seal high temperature leakage test	8
5.5.4 Valve to rim seal peak temperature leakage test	9
5.6 Valve mechanical resistance	9
5.6.1 Over torque nut test	9
5.6.2 High pressure test	9
5.6.3 Radial force resistance (nose resistance)	9
5.7 Environmental resistance	11
5.7.1 Ozone test	11
5.7.2 Neutral salt spray (NSS) test	12