

ISO 22762-3:2024-09 (E)

Elastomeric seismic-protection isolators - Part 3: Applications for buildings - Specifications

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Symbols | 3 |
| 5 | Classification | 6 |
| 5.1 | General | 6 |
| 5.2 | Classification by construction | 7 |
| 5.3 | Classification by tolerance on shear properties | 8 |
| 6 | Requirement | 8 |
| 6.1 | General | 8 |
| 6.2 | Type tests and routine tests | 9 |
| 6.3 | Functional requirements | 10 |
| 6.4 | Design compressive force and design shear displacement | 10 |
| 6.5 | Performance requirements | 10 |
| 6.5.1 | General | 10 |
| 6.5.2 | Compressive properties | 11 |
| 6.5.3 | Shear properties | 12 |
| 6.5.4 | Tensile properties | 12 |
| 6.5.5 | Dependences of shear properties | 13 |
| 6.5.6 | Dependences of compressive properties | 14 |
| 6.5.7 | Shear displacement capacity | 15 |
| 6.5.8 | Durability | 15 |
| 6.6 | Rubber material requirements | 16 |
| 6.6.1 | General | 16 |
| 6.6.2 | Tensile properties | 16 |
| 6.6.3 | Properties after ageing in air | 16 |
| 6.6.4 | Hardness | 17 |
| 6.6.5 | Ozone resistance | 17 |
| 6.6.6 | Other properties | 17 |
| 6.7 | Dimensional requirements | 17 |
| 6.8 | Requirements on steel used for flanges and reinforcing plates | 18 |
| 6.9 | Requirement on lead material for LRB | 19 |
| 7 | Design rules | 19 |
| 7.1 | General | 19 |
| 7.2 | Shape factor | 19 |
| 7.2.1 | First shape factor | 19 |
| 7.2.2 | Second shape factor | 20 |
| 7.3 | Compression and shear properties | 20 |
| 7.3.1 | Compressive stiffness | 20 |
| 7.3.2 | Shear stiffness and equivalent damping ratio | 20 |
| 7.4 | Ultimate properties | 21 |

| | | |
|--|--|----|
| 7.4.1 | Stability at zero displacement | 21 |
| 7.4.2 | Stability and failure under large shear displacements | 22 |
| 7.4.3 | Roll-out properties of elastomeric isolators with recessed or dowelled connections (Type III) | 22 |
| 7.4.4 | Tensile properties | 23 |
| 7.5 | Reinforcing steel plates | 24 |
| 7.6 | Connections | 24 |
| 8 | Manufacturing tolerances | 24 |
| 8.1 | General | 24 |
| 8.2 | Measuring instruments | 25 |
| 8.3 | Plan dimensions | 25 |
| 8.3.1 | Measurement method | 25 |
| 8.3.2 | Tolerances | 25 |
| 8.4 | Product height | 26 |
| 8.4.1 | Measurement method | 26 |
| 8.4.2 | Tolerances | 27 |
| 8.5 | Flatness | 27 |
| 8.5.1 | Measurement method | 27 |
| 8.5.2 | Tolerances | 27 |
| 8.6 | Horizontal offset | 27 |
| 8.7 | Plan dimensions of flanges | 28 |
| 8.8 | Flange thickness | 28 |
| 8.9 | Tolerances on positions of flange bolt holes | 29 |
| 9 | Marking and labelling | 29 |
| 9.1 | General | 29 |
| 9.2 | Information to be provided | 29 |
| 9.3 | Additional requirements | 30 |
| 9.4 | Marking and labelling examples | 30 |
| 10 | Test methods | 30 |
| 11 | Quality assurance | 30 |
| Annex A (normative) Tensile stress in reinforcing steel plate | | 31 |
| Annex B (normative) Determination of ultimate property diagram based on experimental results | | 33 |
| Annex C (informative) Minimum recommended physical properties of rubber material | | 36 |
| Annex D (informative) Effect of inner-hole diameter and second shape factor on shear properties .. | | 37 |
| Annex E (informative) Determination of compressive properties of elastomeric isolators | | 40 |
| Annex F (informative) Determination of shear properties of elastomeric isolators | | 43 |
| Annex G (informative) Method of predicting buckling limit at large deformations | | 48 |
| Annex H (informative) Design of fixing bolts and flanges | | 55 |
| Bibliography | | 58 |