

ISO/PAS 25091:2026-03 (E)

Angular sweep test methods for radio frequency identification (RFID) enabled tyres

| Contents | | Page |
|--|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Angular sweep methods (ASM) | 2 |
| 4.1 | Technical scope | 2 |
| 4.2 | General operating conditions | 3 |
| 4.3 | Angular exploration | 3 |
| 4.3.1 | Introduction | 3 |
| 4.3.2 | Angular sweep specification | 4 |
| 4.4 | Tag position on the radio frequency identification (RFID) enabled tyre | 4 |
| 4.5 | Considerations of the wheel and the immediate surroundings of the tyre | 5 |
| 4.6 | Measuring distance | 5 |
| 4.7 | Angular sweep method (ASM) A | 6 |
| 4.7.1 | General | 6 |
| 4.7.2 | Method layout | 6 |
| 4.7.3 | Angular data points | 8 |
| 4.7.4 | Measuring process | 8 |
| 4.8 | Angular sweep method (ASM) B | 9 |
| 4.8.1 | General | 9 |
| 4.8.2 | Method layout | 9 |
| 4.8.3 | Angular window | 10 |
| 4.8.4 | Measuring process | 12 |
| Annex A (informative) Angular sweep method (ASM) test report for radio frequency identification (RFID) enabled tyres | | 14 |
| Annex B (informative) Angular sweep performance (ASP) indicator calculation | | 16 |
| Annex C (informative) Angular sweep method (ASM) exploratory applications | | 20 |
| Bibliography | | 22 |