

ISO 18164:2026-08 (E)

Motorcycle tyres rolling resistance measurement methods - Single point test

Contents	Page
Foreword	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Test methods	2
5 Test equipment	2
5.1 Drum specifications	2
5.1.1 Diameter	2
5.1.2 Surface	3
5.1.3 Width	3
5.2 Test rim	3
5.3 Load, alignment, control and instrumentation accuracies	3
5.4 Thermal environment	3
5.4.1 Reference conditions	3
5.4.2 Alternative conditions	3
5.4.3 Drum surface temperature	3
6 Test conditions	3
6.1 General	3
6.2 Test speeds	3
6.2.1 Single test speed	3
6.3 Test load	4
6.4 Test inflation pressure	4
6.5 Duration and speed	4
7 Test procedure	4
7.1 General	4
7.2 Thermal conditioning	4
7.3 Pressure adjustment	4
7.4 Warm-up	4
7.5 Measurement and recording	4
7.6 Measurement of parasitic losses	5
7.6.1 General	5
7.6.2 Skim test reading	5
7.6.3 Machine reading	6
7.6.4 Deceleration method	6
7.7 Allowance for machines exceeding sigma m criterion	6
8 Data interpretation	6
8.1 Calculation of parasitic losses	6
8.1.1 General	6
8.1.2 Force method at tyre spindle	7
8.1.3 Torque method at drum axis	7
8.1.4 Power method at drum axis	7
8.1.5 Deceleration method	7
8.2 Rolling resistance calculation	8
8.2.1 General	8

8.2.2	Force method at tyre spindle	8
8.2.3	Torque method at drum axis	8
8.2.4	Power method at drum axis	8
8.2.5	Deceleration method	8
9	Data analysis	9
9.1	Rolling resistance coefficient	9
9.2	Temperature correction	9
9.3	Drum diameter correction	9
9.4	Measurement result and rounding	10
Annex A (informative) Measurement methods of moment of inertia for drum and tyre assembly -- Deceleration method		11
Annex B (normative) Test equipment tolerances		16
Annex C (informative) Example for machine drift evaluation		19
Bibliography		21