ISO 4209-1:2001-09 (E)

Truck and bus tyres and rims (metric series) - Part 1: Tyres

Contents

Page

Foreword v

1 Scope 1

2 Normative reference 1

3 Terms and definitions 1

4 Tyre designation 1
4.1 Content 1
4.2 Size and construction 2
4.2.1 Marking 2
4.2.2 Nominal section width 2
4.2.3 Nominal aspect ratio 2
4.2.4 Tyre construction code 2
4.2.5 Nominal rim diameter 2
4.3 Service condition characteristics 2
4.3.1 Marking 2
4.3.2 Load index 3
4.3.3 Speed symbol 3
4.4 Other service characteristics 3
4.5 Example 3

5 Tyre dimensions 4
5.1 Calculation of "design" tyre dimensions 4
5.1.1 Coefficients 4
5.1.2 Theoretical rim width, Rth 4
5.1.3 Measuring rim width, Rm 4
5.1.4 Design tyre section width, S 4
5.1.5 Design tyre section height, H 4
5.1.6 Design tyre overall diameter, Do 4
5.1.7 Values 5
5.2 Calculation of "maximum overall tyre dimensions in service" 5
5.2.1 Maximum overall width in service, Wmax 5
5.2.2 Maximum overall diameter in service, Do,max 5
5.3 Minimum dual spacing (MDS) 5
5.4 Approved rim widths 7

6 Tyre dimension tables 8

7 Method of measurement of tyre dimensions 8

8 Service characteristics 8
8.1 Tyre load-carrying capacity 8
8.2 Speed symbol 8
8.3 Load-carrying capacity at various speeds 9

Annex A (informative) Guideline values for metric series, 5° rims 12

Annex B (informative) Guideline values for metric series, 15° rims 15

Annex C (informative) Tyre dimension tables 19