

# ISO 2790:2004-09 (E)

## Belt drives - V-belts for the automotive industry and corresponding pulleys - Dimensions

---

| <b>Contents</b> |   | <b>Page</b> |
|-----------------|---|-------------|
| <b>1</b>        | <b>Scope .....</b>  | <b>1</b>    |
| <b>2</b>        | <b>Normative references .....</b>   | <b>1</b>    |
| <b>3</b>        | <b>Terms, definitions and symbols .....</b>                                 | <b>1</b>    |
| <b>4</b>        | <b>Belts .....</b>  | <b>1</b>    |
| <b>4.1</b>      | <b>General .....</b>  | <b>1</b>    |
| <b>4.2</b>      | <b>Cross-section and pitch zone .....</b>                                   | <b>1</b>    |
| <b>4.3</b>      | <b>Measurement of the effective length of a belt and its ride-out .....</b> | <b>2</b>    |
| <b>4.4</b>      | <b>Centre distance variations .....</b>                                     | <b>4</b>    |
| <b>5</b>        | <b>Service pulleys .....</b>  | <b>4</b>    |
| <b>5.1</b>      | <b>Dimensions .....</b>   | <b>4</b>    |
| <b>5.2</b>      | <b>Checking of effective diameter .....</b>                                 | <b>6</b>    |
| <b>5.3</b>      | <b>Designation .....</b>  | <b>7</b>    |