

DIN EN 15570:2008-08 (E)

Hardware for furniture - Strength and durability of hinges and their components - Hinges pivoting on a vertical axis

| Contents | | Page |
|---------------------|---|-------------|
| Foreword | | 3 |
| Introduction | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | General test conditions | 6 |
| 4.1 | Preliminary preparation | 6 |
| 4.2 | Test equipment | 6 |
| 4.3 | Application of forces | 6 |
| 4.4 | Tolerances | 6 |
| 4.5 | Sequence of testing | 7 |
| 4.6 | Inspection and assessment of results | 7 |
| 5 | Test apparatus | 7 |
| 5.1 | Masses | 7 |
| 5.2 | Test frame | 7 |
| 5.3 | Particle board properties | 9 |
| 6 | Test procedures and requirements | 9 |
| 6.1 | General | 9 |
| 6.2 | Overload tests | 9 |
| 6.2.1 | Vertical static overload | 9 |
| 6.2.2 | Horizontal static overload | 10 |
| 6.3 | Functional tests | 11 |
| 6.3.1 | General | 11 |
| 6.3.2 | Operating forces | 11 |
| 6.3.3 | 1 st vertical static load test | 13 |
| 6.3.4 | 1 st horizontal static load | 13 |
| 6.3.5 | Slam shut | 13 |
| 6.3.6 | Determination of reference point for the door sagging | 14 |
| 6.3.7 | Durability | 15 |
| 6.3.8 | Deflection (sagging) test | 16 |
| 6.3.9 | 2 nd vertical static load | 17 |
| 6.3.10 | 2 nd horizontal static load | 17 |
| 6.4 | Corrosion resistance | 17 |
| 7 | Test report | 17 |
| Annex A (normative) | Product information system | 19 |
| A.1 | General | 19 |
| A.2 | Field of application | 19 |
| A.3 | The mass and size of the door | 19 |
| A.4 | Adjustment systems and spring and damper mechanisms | 19 |
| A.5 | Corrosion test | 19 |
| Annex B (normative) | Test parameters | 20 |
| Bibliography | | 23 |