

DIN EN 1058:2010-04 (E)

Wood-based panels - Determination of characteristic 5-percentile values and characteristic mean values

| Contents | | Page |
|-----------------------|---|-------------|
| Foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms and definitions | 4 |
| 4 | Symbols | 5 |
| 5 | Reference population | 5 |
| 6 | Determination of characteristic values of mechanical and physical properties | 5 |
| 6.1 | Sampling | 5 |
| 6.2 | Testing | 6 |
| 6.3 | Analysis of data | 6 |
| 6.3.1 | General | 6 |
| 6.3.2 | Strength and stiffness properties | 6 |
| 6.3.3 | Characteristic mean value (50-percentile characteristic value) | 6 |
| 7 | Test report | 6 |
| Annex A (informative) | Calculation of the 5-percentile characteristic value of log-normal distributed test data according to EN 14358 | 7 |
| A.1 | Symbols | 7 |
| A.1.1 | Letter symbols | 7 |
| A.1.2 | Indices | 7 |
| A.2 | Analysis of data | 8 |
| A.2.1 | Characteristic value k_m of test data with unknown coefficient of variation | 8 |
| A.2.2 | Characteristic value k_m of test data with known coefficient of variation | 8 |
| A.3 | Acceptance criteria for a sample | 9 |
| A.4 | Examples of calculation | 9 |
| A.4.1 | Determination of the characteristic value of the modulus of bending $05f$ of particle boards with unknown coefficient of variation: | 9 |
| A.4.2 | Determination of the characteristic value of the modulus of bending $05f$ of particle boards with known coefficient of variation: | 11 |
| Annex B (normative) | Calculation of the characteristic mean value (50-percentile value) of normal distributed test data | 13 |
| B.1 | Symbols | 13 |
| B.1.1 | Letter symbols (see appendix A) | 13 |
| B.1.2 | Indices (see also appendix A) | 13 |
| B.2 | Analysis of data | 13 |
| B.2.1 | 50-percentile characteristic values (characteristic mean values) | 13 |
| B.3 | Acceptance criteria for a sample | 14 |
| B.4 | Examples of calculation | 14 |
| B.4.1 | Determination of the lower 50-percentile characteristic value (lower characteristic mean value) of the modulus of elasticity $\%50EL$ parallel to the production line of OSB of a normal distributed sample with unknown coefficient of variation | 14 |

| | | |
|---------------------------|---|-----------|
| B.4.2 | Determination of the upper 50-percentile characteristic value (upper characteristic mean value) of the density 50U of a normal distributed sample of particle boards with known coefficient of variation | 16 |
| Bibliography | | 17 |