

ISO 27769-2:2009-08 (E)

Wood-based panels - Wet-process fibreboard - Part 2: Requirements

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Expression of specification limits and general requirements	2
4.1	Expression of specification limits	2
4.2	Lower specification limits	2
4.3	Upper specification limits	2
4.4	Density variation, dimension and moisture content requirements	3
5	Requirements for softboards	3
5.1	Requirements for general purpose softboard for use in dry conditions	3
5.2	Requirements for general purpose softboard for use in humid conditions	4
5.3	Requirements for general purpose softboard for use in high-humidity conditions	4
5.4	Requirements for general purpose softboard for use in exterior conditions	4
5.5	Requirements for load-bearing softboard for use in dry conditions	5
5.6	Requirements for load-bearing softboard for use in humid conditions	5
6	Requirements for hardboards	5
6.1	Requirements for general purpose hardboard for use in dry conditions	5
6.2	Requirements for general purpose hardboard for use in humid conditions	6
6.3	Requirements for general purpose hardboard for use in high-humidity conditions	6
6.4	Requirements for general purpose hardboard for use in exterior conditions	7
6.5	Requirements for load-bearing hardboard for use in dry conditions	7
6.6	Requirements for load-bearing hardboard for use in humid conditions	8
Annex A (normative)	Calculation of 5-percentile and 95-percentile values	9
Bibliography		11