

# ISO 27769-2:2009-08 (E)

## Wood-based panels - Wet-process fibreboard - Part 2: Requirements

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>Expression of specification limits and general requirements .....</b>	<b>2</b>
4.1	Expression of specification limits .....	2
4.2	Lower specification limits .....	2
4.3	Upper specification limits .....	2
4.4	Density variation, dimension and moisture content requirements .....	3
<b>5</b>	<b>Requirements for softboards .....</b>	<b>3</b>
5.1	Requirements for general purpose softboard for use in dry conditions .....	3
5.2	Requirements for general purpose softboard for use in humid conditions .....	4
5.3	Requirements for general purpose softboard for use in high-humidity conditions .....	4
5.4	Requirements for general purpose softboard for use in exterior conditions .....	4
5.5	Requirements for load-bearing softboard for use in dry conditions .....	5
5.6	Requirements for load-bearing softboard for use in humid conditions .....	5
<b>6</b>	<b>Requirements for hardboards .....</b>	<b>5</b>
6.1	Requirements for general purpose hardboard for use in dry conditions .....	5
6.2	Requirements for general purpose hardboard for use in humid conditions .....	6
6.3	Requirements for general purpose hardboard for use in high-humidity conditions .....	6
6.4	Requirements for general purpose hardboard for use in exterior conditions .....	7
6.5	Requirements for load-bearing hardboard for use in dry conditions .....	7
6.6	Requirements for load-bearing hardboard for use in humid conditions .....	8
<b>Annex A (normative)</b>	<b>Calculation of 5-percentile and 95-percentile values .....</b>	<b>9</b>
<b>Bibliography .....</b>		<b>11</b>