

# DIN EN 12490:2010-11 (E)

## Durability of wood and wood-based products - Preservative-treated solid wood - Determination of the penetration and retention of creosote in treated wood

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
1	Scope .....	4
2	Normative references .....	4
3	Terms and definitions .....	4
4	Sampling of creosote-treated wood for the determination of penetration and retention .....	5
4.1	General requirements .....	5
4.2	Specific requirements for test samples for the determination of penetration .....	6
4.3	Specific requirements for test samples for the determination of retention .....	6
5	Determination of the penetration of creosote in treated wood .....	6
6	Determination of the retention of creosote in treated wood .....	7
6.1	Reagents .....	7
6.2	Apparatus .....	7
6.3	Preparation of the water trap and the condenser before the extraction .....	9
6.4	Procedure for the extraction of creosote from the composite sample .....	9
6.5	Expression of results .....	10
7	Test report .....	10
Annex A (informative)	Sapwood/heartwood boundary determination .....	12
A.1	Scope .....	12
A.2	Pines .....	12
A.2.1	Reagents .....	12
A.2.2	Procedure .....	12
A.3	Douglas fir .....	13
A.3.1	Reagents .....	13
A.3.2	Procedure .....	13
Annex B (normative)	Density of some selected timber species that are commonly treated with creosote .....	14
Bibliography .....		15