

# DIN EN 12490:2010-11 (E)

**Durability of wood and wood-based products - Preservative-treated solid wood - Determination of the penetration and retention of creosote in treated wood**

---

<b>Contents</b>		<b>Page</b>
<b>Foreword</b>	.....	<b>3</b>
<b>1</b>	<b>Scope</b> .....	<b>4</b>
<b>2</b>	<b>Normative references</b> .....	<b>4</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>4</b>
<b>4</b>	<b>Sampling of creosote-treated wood for the determination of penetration and retention</b> .....	<b>5</b>
4.1	<b>General requirements</b> .....	<b>5</b>
4.2	<b>Specific requirements for test samples for the determination of penetration</b> .....	<b>6</b>
4.3	<b>Specific requirements for test samples for the determination of retention</b> .....	<b>6</b>
<b>5</b>	<b>Determination of the penetration of creosote in treated wood</b> .....	<b>6</b>
<b>6</b>	<b>Determination of the retention of creosote in treated wood</b> .....	<b>7</b>
6.1	<b>Reagents</b> .....	<b>7</b>
6.2	<b>Apparatus</b> .....	<b>7</b>
6.3	<b>Preparation of the water trap and the condenser before the extraction</b> .....	<b>9</b>
6.4	<b>Procedure for the extraction of creosote from the composite sample</b> .....	<b>9</b>
6.5	<b>Expression of results</b> .....	<b>10</b>
<b>7</b>	<b>Test report</b> .....	<b>10</b>
<b>Annex A (informative) Sapwood/heartwood boundary determination</b> .....		<b>12</b>
A.1	<b>Scope</b> .....	<b>12</b>
A.2	<b>Pines</b> .....	<b>12</b>
A.2.1	<b>Reagents</b> .....	<b>12</b>
A.2.2	<b>Procedure</b> .....	<b>12</b>
A.3	<b>Douglas fir</b> .....	<b>13</b>
A.3.1	<b>Reagents</b> .....	<b>13</b>
A.3.2	<b>Procedure</b> .....	<b>13</b>
<b>Annex B (normative) Density of some selected timber species that are commonly treated with creosote</b> .....		<b>14</b>
<b>Bibliography</b> .....		<b>15</b>