

# ISO 16893-2:2010-11 (E)

## Wood-based panels - Particleboard - Part 2: Requirements

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms, definitions and abbreviations .....</b>	<b>2</b>
<b>4</b>	<b>Expression of specification limits and general requirements .....</b>	<b>2</b>
4.1	Expression of specification limits .....	2
4.2	Lower specification limits .....	3
4.3	Upper specification limits .....	3
4.4	Moisture resistance requirement options .....	3
4.5	Density variation, dimension and moisture content requirements .....	4
4.6	Formaldehyde requirements .....	4
4.7	Requirements for load bearing particleboard for use in dry conditions (P-LB REG) .....	4
<b>5</b>	<b>Specific property requirements .....</b>	<b>5</b>
5.1	Requirements for general purpose particleboard for use in dry conditions (P-GP REG) .....	5
5.2	Requirements for furniture type particleboard for use in dry conditions (P-FN REG) .....	5
5.3	Requirements for heavy-duty load bearing particleboard for use in dry conditions (P-HLB REG) .....	6
5.4	Requirements for general purpose particleboard for use in humid conditions (P-GP MR) .....	6
5.5	Requirements for furniture type particleboard for use in humid conditions (P-FN MR) .....	7
5.6	Requirements for load bearing particleboard for use in humid conditions (P-LB MR) .....	8
5.7	Requirements for heavy-duty load bearing particleboard for use in humid conditions (P-HLB MR) .....	9
5.8	Requirements for general purpose particleboard for use in high humid conditions (P-GP HMR) .....	10
5.9	Requirements for furniture type particleboard for use in high humid conditions (P-FN HMR) .....	11
5.10	Requirements for load bearing particleboard for use in high humid conditions (P-LB HMR) .....	12
5.11	Requirements for heavy-duty load bearing particleboard for use in high humid conditions (P-HLB HMR) .....	13
<b>6</b>	<b>Marking .....</b>	<b>13</b>
Annex A (normative)	Calculation of 5-percentile and 95-percentile values .....	14