

# DIN EN 12871:2013-09 (E)

## Wood-based panels - Determination of performance characteristics for load bearing panels for use in floors, roofs and walls

---

<b>Contents</b>		<b>Page</b>
Foreword .....		4
Introduction .....		5
1	Scope .....	6
2	Normative references .....	6
3	Terms and definitions .....	7
4	Symbols and subscripts .....	9
4.1	Symbols .....	9
4.2	Subscripts .....	10
5	General requirements .....	10
5.1	Specification of panels intended for load-bearing application .....	10
5.2	Mechanical properties .....	11
5.2.1	General .....	11
5.2.2	Concentrated load on structural floor or roof decking on joists .....	11
5.2.3	Soft body impact test .....	11
5.3	Sampling .....	11
6	Determination of performance characteristics .....	12
6.1	General Recommendations .....	12
6.1.1	Dimensional tolerances: length and width .....	12
6.1.2	Dimensional tolerances: thickness .....	12
6.1.3	Dimensional changes: linear expansion .....	12
6.1.4	Discrepancy at joints between panels .....	12
6.1.5	Edge profile of tongued and grooved or similar panels .....	12
6.2	Structural floor or roof decking on joists .....	13
6.2.1	General .....	13
6.2.2	Determination of stiffness characteristics (serviceability limit state) for concentrated load .....	13
6.2.3	Determination of the serviceability load corresponding to the elasticity limit .....	13
6.2.4	Determination of $F_{max,k}$ .....	13
6.2.5	Determination of Impact Class for soft body impact .....	13
6.3	Structural wall sheathing on studs .....	14
6.3.1	General .....	14
6.3.2	Soft body impact test .....	15
7	Evaluation .....	15
7.1	Concentrated load .....	15
7.2	Impact load .....	15
8	Report .....	15
Annex A (normative) Modification to EN 1195 .....		17
A.1	Scope .....	17
A.2	Modification to EN 1195 .....	17

<b>Annex B (informative) Proposal for performance requirements .....</b>	<b>18</b>
<b>B.1 Introduction .....</b>	<b>18</b>
<b>B.2 Concentrated load .....</b>	<b>18</b>
<b>B.2.1 General .....</b>	<b>18</b>
<b>B.2.2 Serviceability limit state .....</b>	<b>19</b>
<b>B.2.3 Ultimate limit state .....</b>	<b>19</b>
<b>B.2.4 Increase of span L as a function of roof slope .....</b>	<b>20</b>
<b>B.3 Soft body impact .....</b>	<b>21</b>
<b>B.3.1 General .....</b>	<b>21</b>
<b>B.3.2 Requirements .....</b>	<b>21</b>
<b>Annex C (informative) Example .....</b>	<b>22</b>
<b>C.1 General .....</b>	<b>22</b>
<b>C.2 Features of the end use .....</b>	<b>22</b>
<b>C.2.1 Decking for flooring in housing applications .....</b>	<b>22</b>
<b>C.2.2 Decking for an accessible cold roof (load category I) .....</b>	<b>22</b>
<b>C.3 Type testing values of the component .....</b>	<b>22</b>
<b>C.3.1 Main features of the testing (according to EN 1195) .....</b>	<b>22</b>
<b>C.3.2 Results .....</b>	<b>22</b>
<b>C.4 Values for the calculation parameters .....</b>	<b>23</b>
<b>C.5 Determination of the Limit States of the component and compliance to recommended requirements .....</b>	<b>23</b>
<b>C.5.1 Ultimate Limit State (according to B.2.3) .....</b>	<b>23</b>
<b>C.5.2 Serviceability Limit State (according to B.2.2) .....</b>	<b>24</b>
<b>C.5.3 Summarisation .....</b>	<b>24</b>
<b>Bibliography .....</b>	<b>25</b>