DIN EN 326-2:2014-10 (E)

Wood-based panels - Sampling, cutting and inspection - Part 2: Initial type testing and factory production control (includes Amendment A1:2014)

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 5

4 Symbols and indices 7
4.1 Letter symbols (see also EN 326-1:1994) 7
4.2 Indices (see also EN 326-1:1994) 8

5 Initial type testing (ITT) 9
5.1 General 9
5.2 Initial type testing by variables 9
5.2.1 General 9
5.2.2 Sampling of panels 9
5.2.3 Evaluation 10
5.3 Initial type testing by attributes 11
5.3.1 Sampling 11
5.3.2 Evaluation 12

6 Factory production control 12
6.1 General 12
6.2 Sampling 13
6.2.1 General 13
6.2.2 Dimensional tolerances, squareness and edge straightness 13
6.2.3 Other properties assessed as attributes and not included in 6.2.1 or 6.2.2 13
6.2.4 Sampling and cutting of test pieces 13
6.3 Factory production control by variables 13
6.3.1 Characteristics 13
6.3.2 Product types 14
6.4 Control of production 14
6.4.1 General 14
6.4.2 Factory production control by variables for batch production 15
6.4.3 Factory production control by attributes for batch production 17
6.4.4 Internal records of an established product 18
6.5 Initial inspection of factory and factory production control (FPC) 19
6.6 Continuous surveillance, assessment and approval of the factory production control 20

Annex A (informative) Example of initial type testing by variables - Evaluation of bending strength of particleboards (see 5.2) 21

A.1 Example 21
A.2 Sampling (see 5.1.2) 21
A.3 Test results, records and evaluation (see 5.2.3 and EN 326-1:1994, Clause 7) 22

Annex B (informative) Factory production control by variables - Example: Batch production (see 6.4.2) 23

B.1 General 23

B.2 Sampling 23
B.3 Testing 23
B.4 Calculation and recording of test results of the first sample 23
B.4.1 Example for the case that the first sample of one panel fulfils the panel characteristic requirement 23
B.4.2 Example for the case that the first sample of one panel does not fulfil the panel characteristic requirement 24

Annex C (informative) Example of initial type testing attributes - Evaluation of bonding quality of plywood (see 6.4.3.1) 27

C.1 Example 27
C.2 Sampling plan 27
C.3 Sampling (see 5.3.1) 27
C.4 Test data and evaluation of bond shear strength and apparent cohesive wood fibre failure percentage 27
C.4.1 General 27
C.4.2 First sample 27
C.4.3 Second sample 29
C.5 Single sampling plan 29

Annex D (informative) Control of factory production control records - Examples of the determination of differences between factory testing and external testing (see 6.6) 30

D.1 General 30
D.1.1 Use of unconditioned test pieces 30
D.1.2 Paired testing 30
D.2 Example (1): Swelling in thickness tested according to EN 317 31
D.2.1 Sample of example (1) 31
D.2.2 Control of variability 31
D.3 Example (2): Internal bond tested according to EN 319 33
D.3.1 General 33
D.3.2 Sample of Example (2) 33
D.3.3 Control of variability 33
D.4 Determination of a significant difference between the results from the alternative test procedure and from the standard reference test method 34

Annex E (informative) Example of the calculation of a linear correlation (see 6.6) 36

Annex F (informative) Example of the determination of a significant difference between the results from the alternative test procedure and from the standard reference test method (see 6.6) in accordance with EN 13986 40

F.1 General 40
F.2 Control of variability (see Annex D) 41
F.3 Determination of a significant difference (see Annex D) 42

Bibliography 43