

ISO 12460-3:2015-11 (E)

Wood-based panels - Determination of formaldehyde release - Part 3: Gas analysis method

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Principle | 1 |
| 4 | Reagents | 1 |
| 5 | Apparatus | 2 |
| 5.1 | Main composites of test apparatus (see Figure 1) | 2 |
| 5.2 | Laboratory equipment | 2 |
| 6 | Sampling and preparation of test pieces | 3 |
| 6.1 | Preparation of test pieces | 3 |
| 6.2 | Selection of test pieces for factory production control | 3 |
| 6.3 | Selection of test pieces for other purposes | 4 |
| 6.4 | Selection of test pieces in case of dispute | 4 |
| 7 | Procedure | 4 |
| 7.1 | Number of determinations | 4 |
| 7.2 | Determination of moisture content | 4 |
| 7.3 | Determination of formaldehyde release | 4 |
| 7.4 | Determination of formaldehyde content of the aqueous solutions | 5 |
| 7.4.1 | General | 5 |
| 7.4.2 | Principle | 5 |
| 7.4.3 | Analytical Procedure | 5 |
| 7.4.4 | Calibration curve | 5 |
| 8 | Expression of results | 7 |
| 8.1 | Gas analysis value | 7 |
| 8.2 | Calculation of results | 7 |
| 8.2.1 | Calculation of results of test pieces | 7 |
| 8.2.2 | Calculation of emission report value | 8 |
| 8.3 | Moisture content | 8 |
| 9 | Test report | 8 |
| Bibliography | | 11 |