

DIN EN 15425:2017-05 (E)

Adhesives - One component polyurethane (PUR) for load-bearing timber structures - Classification and performance requirements

Contents		Page
European foreword		3
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
4	Classification	8
5	Requirements	11
5.1	General	11
5.2	Bond strength in longitudinal tensile shear test	11
5.3	Resistance to delamination	12
5.4	Tensile strength perpendicular to the glue line after climatic treatment (acid damage test)	13
5.5	Effect of wood shrinkage on the shear strength	13
5.6	Static load test of multiple glue line specimens in compression shear	13
5.7	Creep deformation test at cyclic climate conditions with specimens loaded in bending shear	13
5.8	Long-term sustained load test at cyclic climate conditions with specimens loaded perpendicular to the glue line ("Glass house test")	14
6	Test methods	14
6.1	General	14
6.2	Determination of longitudinal tensile shear strength	14
6.3	Determination of resistance to delamination	14
6.4	Determination of tensile strength perpendicular to the glue line after climatic treatment (acid damaged test)	14
6.5	Determination of the effect of wood shrinkage on the shear strength	14
6.6	Static load test of multiple glue line specimens in compression shear	14
6.7	Creep deformation test with specimens loaded in bending shear	15
6.8	Long-term sustained load test at cyclic climate conditions with specimens loaded perpendicular to the glue line ("Glass house test")	15
7	Working properties of the adhesive	15
7.1	General	15
7.2	Determination of initial viscosity under reference conditions	15
7.3	Determination of open assembly time under reference conditions	15
7.4	Determination of pressing time under reference conditions	15
8	Marking and labelling	15
Annex A (normative) Climatic treatment prior to shear test		16
Bibliography		17