

# ISO 12460-2:2018 (E)

## Wood-based panels — Determination of formaldehyde release — Part 2: Small-scale chamber method

---

### Contents

|         |  |
|---------|--|
|         | Foreword   |
| 1       | Scope  |
| 2       | Normative references   |
| 3       | Terms and definitions  |
| 4       | General  |
| 5       | Significance and use   |
| 6       | Interferences  |
| 7       | Apparatus  |
| 7.1     | Test chamber   |
| 7.2     | Make-up air  |
| 7.2.1   | General  |
| 7.2.2   | Air circulation  |
| 7.2.3   | Air sampling port  |
| 8       | Hazards  |
| 8.1     | Chromotropic acid reagent treatment  |
| 8.2     | Cleaning chemicals for glassware   |
| 9       | Test specimens   |
| 9.1     | Standard loading ratio   |
| 9.2     | Number of test pieces  |
| 9.3     | Nonstandard sample configuration testing products with single surface exposed          |
| 10      | Sample material handling and specimen conditioning                                     |
| 10.1    | Handling   |
| 10.2    | Conditioning   |
| 11      | Procedure  |
| 11.1    | Test procedure for materials   |
| 11.2    | Air sampling   |
| 11.3    | Analysis of air samples  |
| 11.4    | Absorbance readings  |
| 12      | Calculation  |
| 13      | Report   |
| Annex A | (normative) Conversion factors for formaldehyde, standard solutions, calibration curve |
| A.1     | General  |
| A.2     | Relative humidity conversion factors for formaldehyde                                  |
| A.2.1   | Berge et al. formula   |
| A.2.2   | WKI calculation models   |
| A.2.2.1 | General  |
| A.2.2.2 | Linear model   |
| A.2.2.3 | Exponential model  |
| A.3     | Standard solution A and B  |

- A.3.1 Standardization of Formaldehyde Standard Solution A (1,0 mg/mL)
- A.3.2 Standard Solution B
- A.4 Calibration curve

Page count: 15