ISO 24338:2022-03 (E)

Laminate floor coverings - Determination of abrasion resistance

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Apparatus 2
4.1 Testing machine (for method A and B) (see Figure 1) 2
4.1.1 Test specimen holder (for method A and B) 2
4.1.2 Holding and lifting device (for method A and B) 2
4.1.3 Rubber covered abrasive wheels (for method A) 2
4.1.4 Abrasive paper strips (for method A) 2
4.1.5 Calibration plates (for method A) 3
4.1.6 Suction device (for method A) 3
4.1.7 Revolution-counter (for method A and B) 3
4.2 Grit feeder and accessories (only for method B) 3
4.2.1 General 3
4.2.2 Vacuum cleaning device 4
4.2.3 Abrading material 6
4.2.4 Leather abrading wheels 6
4.2.5 Stopwatch 6
4.2.6 Grit collection container 6
4.2.7 Calibration plates 7
4.2.8 Transparent template to evaluate the wear of the abraded area 7
4.3 Additional material or equipment (method A and B) 7
4.3.1 Weighing equipment 7
4.3.2 Conditioning chamber 7

5 Test specimens 7

6 Procedure of method A 8
6.1 General 8
6.2 Preparation of test specimens and abrasive papers 8
6.3 Preparation of abrasive wheels 9
6.4 Determination of the abrasion rate of abrasive paper 9
6.5 Abrasion of test specimen 9
6.5.1 General 9
6.5.2 Abrasion evaluation method A - octants 9
6.6 Expression of results 10
6.7 Test report 10

7 Procedure of method B 10
7.1 General 10
7.2 Maintenance of the abrading wheels 10
7.3 Operation of the abrader 11
7.3.1 To start the wear test: 11
7.3.2 To halt the wear test: 11
7.4 Calibration 11
7.4.1 Rate of grit flow 11
7.4.2 Abrading capacity 11

7.5 Abrasion of test specimen 12
7.6 Expression of results 12
7.7 Test report 13

Annex A (normative) Calibration and maintenance of abrasion equipment 14

Annex B (normative) Measurement of shore A hardness 18

Bibliography 19