

ISO 4760:2022-05 (E)

Laminate flooring - Topical moisture resistance - Assembled joint

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Materials needed	2
4.1	Planks	2
4.2	Plastic ring	2
4.3	Beaker	2
4.4	Distilled or de-ionized water	2
4.5	Dye colour	2
4.6	Sealant	2
4.7	Measuring device	2
5	Conditioning	3
6	Procedure	3
6.1	Assembling the test specimen	3
6.1.1	Inspection	3
6.1.2	Cutting	3
6.1.3	Cleaning	4
6.1.4	Assembly	4
6.1.5	Gaps	4
6.1.6	Test positions	5
6.1.7	Sealant	6
6.1.8	Ring placement	6
6.1.9	Weights	7
6.1.10	Zeroing gauge	8
6.1.11	Initial height measurement	8
6.1.12	Water	9
6.1.13	Wet swell exposure	10
6.2	Qualitative rating for wet swell	10
6.3	Quantitative rating for wet swell	10
6.4	Qualitative rating for recovery swell	10
6.5	Quantitative rating for recovery swell	10
7	Rating	10
7.1	Qualitative rating	10
7.2	Quantitative wet swell	12
7.3	Qualitative rating and quantitative recovery swell	12
8	Calculations	12
8.1	Surface swell calculation	12
8.1.1	General	12
8.1.2	Wet swell sample average	12
8.1.3	Wet swell final average	12
8.1.4	Qualitative wet swell rating final average	12

8.2	Recovery swell measurements	13
8.2.1	General	13
8.2.2	Recovery swell calculation	13
8.2.3	Recovery swell sample average	13
8.2.4	Recovery swell final average	13
8.2.5	Qualitative recovery swell rating final average	13
9	Statistics - Precision and bias - Interlaboratory studies	13
10	Report	14
	Annex A (informative) Seam/joint swell - Table of individual results	15
	Annex B (informative) Example of photos to match with subjective ratings	16
	Annex C (informative) Topical moisture resistance worksheet - Surface swell evaluation worksheet	19
	Annex D (informative) Water tightness of the joints	20
	Bibliography	21