ISO 4760:2022-05 (E)

Laminate flooring - Topical moisture resistance - Assembled joint

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Materials needed 2
4.1 Planks 2
4.2 Plastic ring 2
4.3 Beaker 2
4.4 Distilled or de-ionized water 2
4.5 Dye colour 2
4.6 Sealant 2
4.7 Measuring device 2

5 Conditioning 3

6 Procedure 3
6.1 Assembling the test specimen 3
6.1.1 Inspection 3
6.1.2 Cutting 3
6.1.3 Cleaning 4
6.1.4 Assembly 4
6.1.5 Gaps 4
6.1.6 Test positions 5
6.1.7 Sealant 6
6.1.8 Ring placement 6
6.1.9 Weights 7
6.1.10 Zeroing gauge 8
6.1.11 Initial height measurement 8
6.1.12 Water 9
6.1.13 Wet swell exposure 10
6.2 Qualitative rating for wet swell 10
6.3 Quantitative rating for wet swell 10
6.4 Qualitative rating for recovery swell 10
6.5 Quantitative rating for recovery swell 10

7 Rating 10
7.1 Qualitative rating 10
7.2 Quantitative wet swell 12
7.3 Qualitative rating and quantitative recovery swell 12

8 Calculations 12
8.1 Surface swell calculation 12
8.1.1 General 12
8.1.2 Wet swell sample average 12
8.1.3 Wet swell final average 12
8.1.4 Qualitative wet swell rating final average 12

8.2 Recovery swell measurements 13
8.2.1 General 13
8.2.2 Recovery swell calculation 13
8.2.3 Recovery swell sample average 13
8.2.4 Recovery swell final average 13
8.2.5 Qualitative recovery swell rating final average 13

9 Statistics - Precision and bias - Interlaboratory studies 13

10 Report 14

Annex A (informative) Seam/joint swell - Table of individual results 15

Annex B (informative) Example of photos to match with subjective ratings 16

Annex C (informative) Topical moisture resistance worksheet - Surface swell evaluation worksheet 19

Annex D (informative) Water tightness of the joints 20

Bibliography 21