

DIN EN 15316-4-2:2008-09 (E)

Heating systems in buildings - Method for calculation of system energy requirements and system efficiencies - Part 4-2: Space heating generation systems, heat pump systems

| Contents | | Page |
|------------------------------|--|-------------|
| Foreword | | 4 |
| Introduction | | 6 |
| 1 | Scope | 6 |
| 2 | Normative references | 7 |
| 3 | Terms, definitions, symbols and units | 8 |
| 3.1 | Terms and definitions | 8 |
| 3.2 | Symbols and units | 13 |
| 4 | Principle of the method | 15 |
| 4.1 | Heat balance of generation subsystem | 15 |
| 4.2 | Energy input needed to meet the heat requirements | 18 |
| 4.3 | Auxiliary energy WHW,gen,aux | 19 |
| 4.4 | Recoverable, recovered and unrecoverable heat losses | 19 |
| 4.5 | Calculation periods | 19 |
| 4.6 | Calculation by zones | 19 |
| 4.7 | Heat pumps with combined space heating and domestic hot water production | 20 |
| 5 | Generation subsystem calculation | 22 |
| 5.1 | General | 22 |
| 5.2 | Simplified seasonal performance method based on system typology (system typology method) | 22 |
| 5.2.1 | Principle of the system typology method | 22 |
| 5.2.2 | Calculation procedure of the system typology method | 23 |
| 5.3 | Detailed case specific seasonal performance method based on component efficiency (bin-method) | 24 |
| 5.3.1 | Principle of the bin method | 24 |
| 5.3.2 | Input data for the calculation with the bin method | 28 |
| 5.3.3 | Calculation steps to be performed in the bin method | 29 |
| 5.3.4 | Heat energy requirements for space heating and domestic hot water mode for the bins ... | 33 |
| 5.3.5 | Heating capacity and COP at full load | 34 |
| 5.3.6 | COP at part load operation | 38 |
| 5.3.7 | Thermal losses through the generator envelope | 39 |
| 5.3.8 | Calculation of back-up heater | 40 |
| 5.3.9 | Running time of the heat pump | 48 |
| 5.3.10 | Auxiliary energy | 55 |
| 5.3.11 | Total thermal losses and recoverable thermal loss of the generation subsystem | 56 |
| 5.3.12 | Calculation of total energy input | 58 |
| 5.3.13 | Summary of output values | 63 |
| Annex A (informative) | Example of evaluation of meteorological data | 64 |
| Annex B (informative) | Default values of parameters for the case specific seasonal performance method | 69 |
| B.1 | Controller setting of flow temperature (heating characteristic curve) | 69 |

| | | |
|--|---|------------|
| B.2 | Temperature correction factor for domestic hot water storage loading | 70 |
| B.3 | Average water temperature of domestic hot water storages | 70 |
| B.4 | Generator envelope | 70 |
| B.5 | Generation subsystem auxiliaries | 71 |
| B.6 | Factor fcombi for simultaneous operation | 71 |
| B.7 | Temperature reduction factor linked to location | 71 |
| B.8 | Efficiency value of the electrical back-up heater for space heating or DHW operation | 72 |
| Annex C (informative) Calculation method for source and sink temperature correction with fixed exergetic efficiency | | 73 |
| Annex D (informative) Calculation example | | 77 |
| D.1 | Detailed calculation example | 77 |
| D.1.1 | System configuration | 77 |
| D.1.2 | Input data for the calculation (according to 5.3.2) | 77 |
| D.1.3 | Calculation | 80 |
| D.2 | Calculation example (spreadsheet format) | 99 |
| D.2.1 | System configuration | 99 |
| D.2.2 | Input data for the calculation (according to 5.3.2) | 99 |
| D.2.3 | Calculation | 100 |
| Annex E (informative) Example for tabulated values of the system typology method as national annex for the Netherlands | | 104 |
| E.1 | General | 104 |
| E.2 | Scope | 104 |
| E.3 | References | 104 |
| E.4 | Heat pump seasonal performance | 104 |
| E.4.1 | Residential buildings | 104 |
| E.4.2 | Non-residential buildings | 105 |
| E.5 | Heat pump installation efficiency | 106 |
| E.6 | Heat pump installation energy consumption | 108 |
| E.7 | Heat pump installation auxiliary energy consumption | 108 |
| Annex F (informative) Example values for parameters to accomplish the case specific heat pump calculation method (bin method) | | 109 |
| F.1 | General | 109 |
| F.2 | Temperatures | 109 |
| F.2.1 | Source temperatures | 109 |
| F.3 | Example values for heating capacity and coefficient of performance for electrically driven heat pumps | 111 |
| F.3.1 | General | 111 |
| F.3.2 | Heating capacity | 111 |
| F.3.3 | COP | 114 |
| F.4 | Gas engine-driven heat pumps | 116 |
| F.4.1 | Preface | 116 |
| F.4.2 | Heating capacity | 117 |
| F.4.3 | COP | 119 |
| F.5 | Absorption heat pumps | 121 |
| F.5.1 | General | 121 |
| F.5.2 | NH3/H2O heat pumps - outside air-to-water | 122 |
| F.5.3 | NH3/H2O heat pumps - brine-to-water | 123 |
| F.5.4 | NH3/H2O heat pumps - water-to-water | 124 |
| F.5.5 | H2O/LiBr double effect heat pumps | 125 |
| F.6 | Heat pumps with domestic hot water production (DHW) - Heating capacity of domestic hot water heat pumps | 126 |
| Bibliography | | 127 |