

DIN EN 13141-2:2010-12 (E)

Ventilation for buildings - Performance testing of components/products for residential ventilation - Part 2: Exhaust and supply air terminal devices

| Contents | Page |
|--|------|
| Foreword | 3 |
| 1 Scope | 6 |
| 2 Normative references | 6 |
| 3 Terms and definitions | 7 |
| 4 Performance testing of aerodynamic characteristics | 7 |
| 4.1 Flow rate/pressure | 7 |
| 4.1.1 Principle | 7 |
| 4.1.2 Test installation, conditions and uncertainty of measurement | 7 |
| 4.1.3 Test procedure | 9 |
| 4.1.4 Analysis of results | 10 |
| 4.1.5 Presentation of results | 10 |
| 4.2 Air diffusion characteristics for supply air terminal devices | 10 |
| 5 Performance testing of acoustic characteristics | 10 |
| 5.1 Noise production for components of systems | 10 |
| 5.1.1 General | 10 |
| 5.1.2 Test installation | 10 |
| 5.1.3 Test procedure | 12 |
| 5.1.4 Acoustic measurement | 13 |
| 5.1.5 Presentation of results | 14 |
| 5.2 Insertion loss of component of systems | 14 |
| 5.2.1 General | 14 |
| 5.2.2 Test procedure | 14 |
| 5.2.3 Preparation and mounting of the test samples | 16 |
| 5.2.4 Procedure | 16 |
| 5.2.5 Control of the limiting insertion loss | 18 |
| 5.2.6 Calculations | 18 |
| 5.2.7 Expression of results | 19 |
| 5.3 Sound insulation characteristics of a pair of air terminal devices | 19 |
| 5.3.1 General | 19 |
| 5.3.2 Testing without airflow | 21 |
| 5.3.3 Testing with airflow | 21 |
| 5.3.4 Conditions for measuring background noise | 21 |
| 5.3.5 Presentation of the results | 22 |
| Bibliography | 23 |