

ISO/IEC 14908-2:2012-02 (E)

Information technology - Control network protocol - Part 2: Twisted pair communication

Contents		Page
Introduction		5
1	Scope	7
2	Normative references	7
3	Network overview	7
4	System specifications	7
4.1	General aspects	7
4.2	Cable	8
4.3	Topology	8
4.3.1	Free or bus topology	8
4.3.2	Repeater	8
4.4	Cable Termination	8
4.4.1	Free-topology segment	8
4.4.2	Bus topology segment	8
4.5	Segment configuration	9
4.6	Power specifications	9
5	Link power	9
5.1	General	9
5.2	Source	10
5.3	Power supply requirements	10
5.4	Passive coupler circuit	13
6	Node specifications	14
6.1	Link power	14
6.2	Hot plugging	14
6.3	Transmitter/receiver interface to the MAC sub-layer	14
6.3.1	Physical layer protocol data unit	14
6.3.2	Frame format	15
6.3.3	Transmit waveform	16
6.4	Impedance	19
7	Communication parameters	20
Annex A (informative)		21
Environmental specifications		21
Bibliography		22

Figures

Figure 1 — Termination.....	8
Figure 2 — Link Power Source.....	10
Figure 3 — Power supply output ripple voltage requirement	11
Figure 4 — Power supply startup interval behavior	12
Figure 5 — Coupler circuit schematic.....	13
Figure 6 — Physical layer protocol data unit	15
Figure 7 — Frame format for compliant transmitter.	15
Figure 8 — Idealised transmit waveform - zero bit.....	16
Figure 9 — Idealised transmit waveform - one bit.....	17
Figure 10 — Maximum voltage spectrum over frequency relative to peak.....	18
Figure 11 — Minimum impedance – powered and unpowered node	19

Tables

Table 1 — Bus-Topology Distance Specifications	9
Table 2 — Free-Topology distance specifications	9
Table 3 — Power supply requirements.....	11
Table 4 — Coupler circuit bill of materials	14
Table 5 — Link power requirements.....	14
Table 6 — Communication parameters for interoperable transceiver	20
Table A. 1 —Representative environmental specifications for nodes	21