ISO/IEC 14908-2:2012-02 (E)

Information technology - Control network protocol - Part 2: Twisted pair communication

Contents

Page

Introduction 5

1 Scope 7

2 Normative references 7

3 Network overview 7

4 System specifications 7
4.1 General aspects 7
4.2 Cable 8
4.3 Topology 8
4.3.1 Free or bus topology 8
4.3.2 Repeater 8
4.4 Cable Termination 8
4.4.1 Free-topology segment 8
4.4.2 Bus topology segment 8
4.5 Segment configuration 9
4.6 Power specifications 9

5 Link power 9
5.1 General 9
5.2 Source 10
5.3 Power supply requirements 10
5.4 Passive coupler circuit 13

6 Node specifications 14
6.1 Link power 14
6.2 Hot plugging 14
6.3 Transmitter/receiver interface to the MAC sub-layer 14
6.3.1 Physical layer protocol data unit 14
6.3.2 Frame format 15
6.3.3 Transmit waveform 16
6.4 Impedance 19

7 Communication parameters 20

Annex A (informative) 21

Environmental specifications 21

Bibliography 22

Figures

Figure 1 — Termination 8
Figure 2 — Link Power Source 10
Figure 3 — Power supply output ripple voltage requirement 11
Figure 4 — Power supply startup interval behavior 12
Figure 5 — Coupler circuit schematic 13
Figure 6 — Physical layer protocol data unit 15
Figure 7 — Frame format for compliant transmitter. 15
Figure 8 — Idealised transmit waveform - zero bit 16
Figure 9 — Idealised transmit waveform - one bit 17
Figure 10 — Maximum voltage spectrum over frequency relative to peak 18
Figure 11 — Minimum impedance – powered and unpowered node 19

Tables

Table 1 — Bus-Topology Distance Specifications 9
Table 2 — Free-Topology distance specifications 9
Table 3 — Power supply requirements 11
Table 4 — Coupler circuit bill of materials 14
Table 5 — Link power requirements 14
Table 6 — Communication parameters for interoperable transceiver 20
Table A. 1 —Representative environmental specifications for nodes 21