

# ISO/IEC 14908-2:2012-02 (E)

## Information technology - Control network protocol - Part 2: Twisted pair communication

---

<b>Contents</b>		<b>Page</b>
Introduction .....		5
1	Scope .....	7
2	Normative references .....	7
3	Network overview .....	7
4	System specifications .....	7
4.1	General aspects .....	7
4.2	Cable .....	8
4.3	Topology .....	8
4.3.1	Free or bus topology .....	8
4.3.2	Repeater .....	8
4.4	Cable Termination .....	8
4.4.1	Free-topology segment .....	8
4.4.2	Bus topology segment .....	8
4.5	Segment configuration .....	9
4.6	Power specifications .....	9
5	Link power .....	9
5.1	General .....	9
5.2	Source .....	10
5.3	Power supply requirements .....	10
5.4	Passive coupler circuit .....	13
6	Node specifications .....	14
6.1	Link power .....	14
6.2	Hot plugging .....	14
6.3	Transmitter/receiver interface to the MAC sub-layer .....	14
6.3.1	Physical layer protocol data unit .....	14
6.3.2	Frame format .....	15
6.3.3	Transmit waveform .....	16
6.4	Impedance .....	19
7	Communication parameters .....	20
Annex A (informative) .....		21
Environmental specifications .....		21
Bibliography .....		22

## Figures

Figure 1 — Termination.....	8
Figure 2 — Link Power Source.....	10
Figure 3 — Power supply output ripple voltage requirement .....	11
Figure 4 — Power supply startup interval behavior .....	12
Figure 5 — Coupler circuit schematic.....	13
Figure 6 — Physical layer protocol data unit .....	15
Figure 7 — Frame format for compliant transmitter. ....	15
Figure 8 — Idealised transmit waveform - zero bit.....	16
Figure 9 — Idealised transmit waveform - one bit.....	17
Figure 10 — Maximum voltage spectrum over frequency relative to peak.....	18
Figure 11 — Minimum impedance – powered and unpowered node .....	19

## Tables

Table 1 — Bus-Topology Distance Specifications .....	9
Table 2 — Free-Topology distance specifications .....	9
Table 3 — Power supply requirements.....	11
Table 4 — Coupler circuit bill of materials .....	14
Table 5 — Link power requirements.....	14
Table 6 — Communication parameters for interoperable transceiver .....	20
Table A. 1 —Representative environmental specifications for nodes .....	21