DIN EN 12977-2:2012-06 (E)

Thermal solar systems and components - Custom built systems - Part 2: Test methods for solar water heaters and combisystems

Contents

Page

Foreword 4

Introduction 5

1 Scope 8

2 Normative references 8

3 Terms and definitions 9

4 Symbols and abbreviations 10

5 System classification 12

6 Test methods 12
6.1 Introduction 12
6.2 General 12
6.3 Materials 13
6.4 Components and pipework 13
6.5 Safety equipment and indicators 15
6.6 Installation 16
6.7 Initial operation, inspection and commissioning 16
6.8 Documentation 17
6.9 System performance (for small systems only) 17
6.10 Water wastage (for small systems only) 17

7 Optional performance test of small custom built solar heating systems 17
7.1 General 17
7.2 Test of the solar collector 18
7.3 Test of the water store(s) 18
7.4 Test of the control equipment 18
7.5 Determination of the hot water comfort 18
7.6 System simulation model 19
7.7 Long-term performance prediction 19
7.8 Presentation of performance indicators 25

8 Performance test report 26

Annex A (normative) Reference conditions for performance prediction 28

A.1 General 28
A.2 Pipe diameter and insulation thickness 30
A.3 Calculation of mains water temperature at reference location 30
A.4 Space heating load 31

Annex B (normative) Additional information regarding the calculation of the fractional energy savings 37

B.1 Definition of a conventional reference water heating system 37
B.2 Calculation of fractional energy savings for other conditions 37

Annex C (informative) Short-term system testing 39

C.1 General 39
C.2 Instrumentation, data acquisition and processing 39
C.3 Check of short-term system performance 41
C.4 Short-term test for long-term system performance prediction 44

Annex D (informative) Long-term monitoring 51

D.1 General 51
D.2 Evaluation chart 52
D.3 Monitoring equipment 52
D.4 Data analysis 52

Annex E (informative) Determination of water wastage 53

Bibliography 54

Figures Figure 1 -- Energy balance for one-store and two-store solar-plus-supplementary systems 21

Figure 2 -- Comparison of the gross auxiliary energy demand of the solar heating system, Qaux, to the gross energy demand of the conventional heating system, Qconv 22

Figure 3 -- Energy balance for solar only systems 24

Figure 4 -- Energy balance for solar preheat systems 25

Figure C.1 -- Principle of the short term system performance check: Check and intercomparison of useful energy gain 41

Figure C.2 -- Principle of the short-term test and of the subsequent long term system performance prediction 45

Figure C.3 -- Example of the predicted performance dependence on load level and irradiation for a solar domestic hot water heating system (see [8]) 50

Tables Table 1 -- Division for factory made and custom built solar heating systems 6

Table 2 -- Symbols, definition and unit (1 of 2) 10

Table 2 -- Symbols, definition and unit (2 of 2) 11

Table 3 -- Presentation of system performance indicators for solar-plus-supplementary systems ... 26

Table 4 -- Presentation of system performance indicators for solar-only and solar preheat systems 26

Table A.1 -- Reference conditions for performance presentation (1 of 2) 28

Table A.1 -- Reference conditions for performance presentation (2 of 2) 29

Table A.2 -- External pipe diameter and insulation thickness for forced-circulation systems 30

Table A.3 -- Data for calculation of the mains water temperature at the reference locations 31

Table A.4 -- Space heating load file for Stockholm 32

Table A.5 -- Space heating load file for Davos 33

Table A.6 -- Space heating load file for Würzburg (1 of 2) 34

Table A.6 -- Space heating load file for Würzburg (2 of 2) 35

Table A.7 -- Space heating load file for Athens - Example to be updated 36

Table C.1 -- Variables to be measured and corresponding maximum sampling intervals 43

Table C.2 -- Variables to be measured during system test, and corresponding maximum sampling intervals 46

Table C.3 -- Range of variations of the driving variables to be scanned during a test outdoors 47

Table C.4 -- Permissible standard deviation for secondary collector parameters 49