

# DIN EN 253:2013-05 (E)

District heating pipes - Preinsulated bonded pipe systems for directly buried hot water networks - Pipe assembly of steel service pipe, polyurethane thermal insulation and outer casing of polyethylene (includes Amendment A1:2013)

---

<b>Contents</b>		<b>Page</b>
page	Foreword .....	4
	Introduction .....	5
<b>1</b>	<b>Scope .....</b>	<b>6</b>
<b>2</b>	<b>Normative references .....</b>	<b>6</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>7</b>
<b>4</b>	<b>Requirements .....</b>	<b>9</b>
4.1	General .....	9
4.2	Steel service pipe .....	9
4.2.1	Specification .....	9
4.2.2	Diameter .....	10
4.2.3	Wall thickness .....	10
4.2.4	Surface condition .....	12
4.3	Casing .....	12
4.3.1	Material properties .....	12
4.3.2	Casing properties .....	13
4.4	Polyurethane rigid foam insulation (PUR) .....	15
4.4.1	Composition .....	15
4.4.2	Voids and bubbles .....	15
4.4.3	Compressive strength .....	15
4.5	Pipe assembly .....	15
4.5.1	General .....	15
4.5.2	Pipe ends .....	15
4.5.3	Diameter and wall thickness of the casing .....	15
4.5.4	Centre line deviation .....	16
4.5.5	Expected thermal life and long term temperature resistance .....	17
4.5.6	Thermal conductivity in unaged condition .....	17
4.5.7	Thermal conductivity at artificially aged condition .....	17
4.5.8	Impact resistance .....	17
4.5.9	Long term creep resistance and modulus .....	17
4.5.10	Surface conditions at delivery .....	18
4.5.11	Measuring wires for surveillance systems .....	18
<b>5</b>	<b>Test methods .....</b>	<b>18</b>
5.1	General conditions and test specimens .....	18
5.1.1	General conditions .....	18
5.1.2	Test specimens .....	18
5.2	Casing .....	19
5.2.1	Appearance and surface finish .....	19
5.2.2	Elongation at break .....	19
5.2.3	Carbon black dispersion, homogeneity .....	20
5.2.4	Stress crack resistance test .....	20
5.3	Polyurethane rigid foam insulation (PUR) .....	21
5.3.1	Composition .....	21
5.3.2	Voids and bubbles .....	21

5.3.3	Compressive strength .....	21
5.4	Pipe assembly .....	21
5.4.1	Axial shear strength .....	21
5.4.2	Tangential shear strength .....	23
5.4.3	Shear strength of the pipe assembly after ageing .....	25
5.4.4	Thermal conductivity in unaged condition .....	26
5.4.5	Thermal conductivity at artificially aged condition .....	26
5.4.6	Impact resistance .....	26
5.4.7	Long term creep resistance and modulus at 140 °C .....	26
6	Marking .....	30
6.1	General .....	30
6.2	Steel service pipe .....	30
6.3	Casing .....	30
6.4	Pipe assembly .....	30
Annex A (informative) Relation between actual continuous operating conditions and accelerated ageing test conditions .....		31
Annex B (informative) Calculation of the minimum expected thermal life with operation at various temperatures with respect to PUR foam performance .....		33
Annex C (normative) "Calculated Continuous Operating Temperature (CCOT)" .....		34
Annex D (informative) Guidelines for inspection and testing .....		37
D.1	General .....	37
D.2	Manufacturer's type test .....	37
D.3	Manufacturer's quality control .....	37
D.4	External inspection .....	37
D.5	Manufacturer's responsibility .....	37
Annex E (informative) Radial creep behaviour of the polyurethane foam (PUR) .....		40
Annex F (normative) Thermal conductivity of pre-insulated pipes - Test procedure .....		41
F.1	Scope .....	41
F.2	Requirements (EN ISO 8497:1996, Clause 5) .....	41
F.2.1	Test specimen (EN ISO 8497:1996, 5.1) .....	41
F.2.2	Operating temperature (EN ISO 8497:1996, 5.2) .....	41
F.2.3	Types of apparatus (EN ISO 8497:1996, 5.5) .....	41
F.3	Apparatus (EN ISO 8497:1996, Clause 7) .....	41
F.3.1	Guarded end apparatus .....	41
F.3.2	Calibrated end apparatus .....	41
F.3.3	Dimensions (EN ISO 8497:1996, 7.2) .....	42
F.3.4	Heater pipe surface temperature .....	42
F.4	Test specimens (EN ISO 8497:1996, Clause 8) .....	42
F.4.1	Conditioning (EN ISO 8497:1996, 8.4) .....	42
F.4.2	Dimension measurement (EN ISO 8497:1996, 8.5) .....	42
F.4.3	Surface temperature measurement .....	42
F.4.4	Location of temperature sensors (EN ISO 8497:1996, 8.6) .....	42
F.5	Procedure (EN ISO 8497:1996, Clause 9) .....	42
F.5.1	Test length (EN ISO 8497:1996, 9.1.1) .....	42
F.5.2	Diameter (EN ISO 8497:1996, 8.5) .....	42
F.5.3	Thickness of casing .....	43
F.5.4	Ambient requirements (EN ISO 8497:1996, 9.2) .....	43
F.5.5	Test pipe temperature (EN ISO 8497:1996, 9.3) .....	43
F.5.6	Power supply (EN ISO 8497:1996, 7.9) .....	43
F.5.7	Axial heat loss (EN ISO 8497:1996, 5.7) .....	43
F.5.8	Test period and stability (EN ISO 8497:1996, 9.5.3) .....	43
F.6	Calculations (EN ISO 8497:1996, Clause 11) .....	43
F.6.1	Thermal conductivity (EN ISO 8497:1996, 3.5) .....	43

<b>F.7</b>	<b>Symbols and units (EN ISO 8497:1996 Clause 4)</b> .....	<b>44</b>
	<b>Annex G (informative) National A-deviations</b> .....	<b>46</b>
<b>G.1</b>	<b>Swedish national legislative deviations on steel service pipes</b> .....	<b>46</b>
	<b>Annex I (informative) Waste treatment and recycling</b> .....	<b>49</b>
	<b>Bibliography</b> .....	<b>50</b>