

DIN EN 13757-3:2013-08 (E)

Communication systems for and remote reading of meters - Part 3: Dedicated application layer

| Contents | Page |
|--|-------------|
| Foreword | 8 |
| Introduction | 9 |
| 1 Scope | 10 |
| 2 Normative references | 10 |
| 3 Terms and definitions, abbreviated terms and numbers | 10 |
| 4 General principles: CI-field | 12 |
| 5 Variable Data Send and Variable Data Respond | 17 |
| 6 Variable data blocks (records) | 29 |
| 7 Value Information Block (VIB) | 33 |
| 8 Application layer status and error reporting | 42 |
| 9 Generalised object layer | 45 |
| 10 Manufacturer specific unstructured data block | 45 |
| 11 Management of lower layers | 46 |
| Annex A (normative) Coding of data records | 50 |
| Annex B (normative) Interpretation of hex-codes Ah - Fh in BCD-data fields | 57 |
| Annex C (normative) VIF coding for special units | 58 |
| Annex D (informative) Alarm protocol | 60 |
| Annex E (informative) Examples | 61 |
| Annex F (informative) Secondary search | 69 |
| Annex G (informative) International reference works | 72 |
| Annex H (informative) Special sequences for wireless M-Bus devices | 73 |
| Annex I (normative) Transmission of profiles | 77 |
| Annex J (informative) The structure of higher protocol layers | 82 |
| Annex K (normative) Compact M-Bus frame | 84 |
| Annex L (informative) Use of standards for smart metering applications | 89 |
| Annex M (informative) Installation and registration | 94 |

| | |
|--|-----|
| Annex N (informative) M-Bus data container | 97 |
| Annex O (normative) Translating M-Bus type record descriptors to OBIS-type record descriptors .. | 99 |
| Annex P (informative) Datagram examples for the M-Bus and the wM-Bus | 116 |
| Bibliography | 151 |
| Figures Figure A.1 -- Change of time by daylight savings | 54 |
| Figure F.1 -- Number of selections with wildcard searching procedure | 69 |
| Figure F.2 -- Flow diagram for slave search with wildcards | 70 |
| Tables Table 1 -- CI-field codes used by the master or the slave | 12 |
| Table 2 -- Coding of the upper 4 bits of the first parameter after CI = 50h or 53h | 15 |
| Table 3 -- Variable data structure in answer send and respond direction | 17 |
| Table 4 -- Short data header | 18 |
| Table 5 -- Long data header | 18 |
| Table 6 -- Device type identification | 19 |
| Table 7 -- Coding of the status field | 22 |
| Table 8 -- Application errors coded with the status-field | 22 |
| Table 9 -- Meaning of status byte for partner messages | 23 |
| Table 10 -- General definition of the configuration field | 23 |
| Table 11 -- Definition of the mode bits (encryption method) | 24 |
| Table 12 -- Definition of the configuration field for encryption modes 2 and 3 | 25 |
| Table 13 -- Definition of the configuration field for encryption mode 5 | 26 |
| Table 14 -- Initialisation vector mode 5 for the CBC-AES-128 | 26 |
| Table 15 -- Contents of meter message | 27 |
| Table 16 -- Contents of partner message | 28 |
| Table 17 -- Accessibility of a meter | 28 |
| Table 18 -- Address structure of the wireless link layer | 29 |
| Table 19 -- Structure of a data record (transmitted from left to right) | 29 |
| Table 20 -- Coding of the Data Information Field (DIF) | 30 |
| Table 21 -- Coding of the data field | 30 |
| Table 22 -- DIF-coding for special functions | 31 |
| Table 23 -- Function field | 31 |
| Table 24 -- Coding of the Data Information Field Extension (DIFE) | 32 |

| | |
|--|----|
| Table 25 -- Coding of the Value Information Field (VIF) | 33 |
| Table 26 -- Primary VIF-codes | 34 |
| Table 27 -- Special VIF-codes | 35 |
| Table 28 -- Main VIFE-code extension table | 35 |
| Table 29 -- Alternate extended VIF-code table | 38 |
| Table 30 -- Combinable (orthogonal) VIFE-table | 39 |
| Table 31 -- Extension of combinable VIFE-table (following VIFE = FCh of combinable (orthogonal) VIFE-table) | 41 |
| Table 32 -- Application error (no header) | 42 |
| Table 33 -- Application error (short data header) | 42 |
| Table 34 -- Application error (long data header) | 42 |
| Table 35 -- First error code byte for general application errors | 43 |
| Table 36 -- Codes for record errors (E = Extension bit) | 44 |
| Table 37 -- Action codes for the generalised object layer (master to slave) | 45 |
| Table 38 -- Management layer of the M-Bus link layer according EN 13757-2 | 46 |
| Table 39 -- CI-field codes for baud rate switching | 46 |
| Table 40 --Structure of a datagram for selecting a slave | 47 |
| Table 41 -- Application layer structure of a datagram for enhanced selection (mode 1) | 48 |
| Table A.1 -- Type A: Unsigned BCD | 50 |
| Table A.2 -- Type B: Signed integer | 50 |
| Table A.3 -- Type C: Unsigned integer | 50 |
| Table A.4 -- Type D: Boolean | 51 |
| Table A.5 -- Type F: Date and time (CP32) | 51 |
| Table A.6 -- Type G: Date (CP16) | 51 |
| Table A.7 -- Type H: Floating point | 52 |
| Table A.8 -- Type I: Date and time (CP48) | 53 |
| Table A.9 -- Type J = Time (CP24) | 54 |
| Table A.10 -- Type K: Daylight savings | 55 |
| Table A.11 -- Type L: Listening window management | 56 |
| Table B.1 -- Decoding table | 57 |
| Table C.1 -- Metric/non-metric units | 58 |

| | |
|---|----|
| Table C.2 -- Data record structure for plain text VIF usage | 58 |
| Table C.3 -- Values for the remote control of the valve | 59 |
| Table E.1 -- Data structure for writing data | 62 |
| Table E.2 -- Coding of primary address | 62 |
| Table E.3 -- Coding of single identification number | 62 |
| Table E.4 -- Coding of complete secondary address | 63 |
| Table E.5 -- Structure of secondary address | 63 |
| Table F.1 -- Secondary addresses found with a wildcard search of four slaves | 71 |
| Table H.1 -- Least significant error byte (EF1) | 73 |
| Table H.2 -- Meaning of error bits in the least significant error byte (EF1) | 73 |
| Table H.3 -- Second least significant error byte (EF2) | 73 |
| Table H.4 -- Least significant byte of the remote control (RC1) | 74 |
| Table H.5 -- Remote control (RC1): adjust power | 74 |
| Table H.6 -- Remote control (RC1): enable test mode | 74 |
| Table H.7 -- Remote control (RC1): power save mode | 74 |
| Table H.8 -- Remote control (RC1): reserved | 74 |
| Table H.9 -- Structure of TC-field | 75 |
| Table H.10 -- Application frame "time setting" with CI=6Ch (Set date and time) | 75 |
| Table H.11 -- Application frame "time adjustment" with CI=6Dh (Add/Subtract Time Offset) | 75 |
| Table I.1 -- Example for load profile: plain data | 77 |
| Table I.2 -- Example for load profile: M-Bus-sequence | 77 |
| Table I.3 -- Base value record (connected via storage-, tariff-, subunit number and VIF/ VIFEx) | 78 |
| Table I.4 -- Base time record (connected via the storage number) | 78 |
| Table I.5 -- Profile record (connected via storage-, tariff-, subunit number and VIF/VIFEx) | 78 |
| Table I.6 -- Spacing control byte | 79 |
| Table I.7 -- Structure of spacing control byte | 79 |
| Table I.8 -- Spacing value byte | 79 |
| Table I.9 -- Example of compact profile with registers: Plain data | 80 |
| Table I.10 -- Example of compact profile with registers: M-Bus data records | 81 |
| Table I.11 -- Example of compact profile without registers: Plain data | 81 |
| Table I.12 -- Example of compact profile without registers: M-Bus data records | 81 |

| | |
|--|-----|
| Table J.1 -- Application layer without a fixed header (none) | 82 |
| Table J.2 -- Application layer with a short header | 82 |
| Table J.3 -- Application layer with a long header | 82 |
| Table J.4 -- Transport layer with a short header | 83 |
| Table J.5 -- Transport layer with a long header | 83 |
| Table K.1 -- CI-fields for the Request of Full and Compact and Format M-Bus frame format | 85 |
| Table K.2 -- CI-fields for the Full and Compact and Format M-Bus frame format | 85 |
| Table K.3 -- Structure of Full M-Bus frame | 85 |
| Table K.4 -- Structure of M-Bus-Compact frame | 85 |
| Table K.5 -- Structure of M-Bus-Format frame | 86 |
| Table L.1 -- Required value resolution for meter with power/flow data | 91 |
| Table L.2 -- Required value resolution without power/flow data | 92 |
| Table N.1 -- Structure of data record | 97 |
| Table O.1 -- M-Bus-OBIS-Translation: legend | 100 |
| Table O.2 -- M-Bus-OBIS-Translation: general (for all devices) | 101 |
| Table O.3 -- M-Bus-OBIS-Translation: electricity meter | 102 |
| Table O.4 -- M-Bus-OBIS-Translation: heat cost allocator | 104 |
| Table O.5 -- M-Bus-OBIS-Translation: cooling meter | 105 |
| Table O.6 -- M-Bus-OBIS-Translation: combined heat and cooling meter | 107 |
| Table O.7 -- M-Bus-OBIS-Translation: heat meter | 109 |
| Table O.8 -- M-Bus-OBIS-Translation: gas meter | 111 |
| Table O.9 -- M-Bus-OBIS-Translation: water meter (cold) | 113 |
| Table O.10 -- M-Bus-OBIS-Translation: water meter (hot, warm) | 114 |
| Table P.1 -- SND-NR - Gas meter (wM-Bus) | 116 |
| Table P.2 -- RSP-UD - Gas meter (M-Bus) | 119 |
| Table P.3 -- SND-NR - Water meter (wM-Bus) | 121 |
| Table P.4 -- RSP-UD - Water meter (M-Bus) | 124 |
| Table P.5 -- SND-NR - Heat meter (wM-Bus) | 126 |
| Table P.6 -- RSP-UD - Heat meter (M-Bus) | 129 |
| Table P.7 -- SND-NR - H.C.A. (wM-Bus) | 131 |
| Table P.8 -- RSP-UD - H.C.A. (M-Bus) | 134 |

| | |
|---|------------|
| Table P.9 -- SND-IR (wM-Bus) | 136 |
| Table P.10 -- CNF-IR (wM-Bus) | 140 |
| Table P.11 -- SND-UD (wM-Bus) | 141 |
| Table P.12 -- ACK long (wM-Bus) | 143 |
| Table P.13 -- REQ-UD2 (wM-Bus) | 145 |
| Table P.14 -- RSP-UD (wM-Bus data) | 146 |
| Table P.15 -- RSP-UD (wM-Bus Appl.error) | 147 |
| Table P.16 -- SND-NKE (wM-Bus) | 149 |