

# DIN EN 16445:2013-05 (E)

## Ventilation for buildings - Air diffusion - Aerodynamic testing and rating for mixed flow application: non-isothermal procedure for cold jet

---

| <b>Contents</b>     |   | <b>Page</b> |
|---------------------|---|-------------|
| <b>Foreword</b>     | .....   | <b>3</b>    |
| <b>1</b>            | <b>Scope</b> .....  | <b>4</b>    |
| <b>2</b>            | <b>Normative references</b> .....   | <b>4</b>    |
| <b>3</b>            | <b>Terms and definitions</b> .....  | <b>4</b>    |
| <b>4</b>            | <b>Symbols (and abbreviated terms)</b> .....  | <b>6</b>    |
| <b>5</b>            | <b>Requirements</b> .....   | <b>7</b>    |
| <b>5.1</b>          | <b>Instrumentation</b> .....  | <b>7</b>    |
| <b>5.1.1</b>        | <b>Air flow rate measurement</b> .....  | <b>7</b>    |
| <b>5.1.2</b>        | <b>Temperature measurements</b> .....   | <b>7</b>    |
| <b>5.1.3</b>        | <b>Velocity measurements</b> .....  | <b>7</b>    |
| <b>5.2</b>          | <b>Test room and conditions</b> .....   | <b>7</b>    |
| <b>5.3</b>          | <b>ATD isothermal characteristics</b> .....   | <b>7</b>    |
| <b>6</b>            | <b>Test to measure the non isothermal air discharge characteristics of a supply ATD</b> ..... | <b>8</b>    |
| <b>6.1</b>          | <b>Installation of ATD</b> .....  | <b>8</b>    |
| <b>6.2</b>          | <b>Test procedure for horizontal cold jet</b> .....   | <b>10</b>   |
| <b>6.2.1</b>        | <b>Test conditions</b> .....  | <b>10</b>   |
| <b>6.2.2</b>        | <b>Preliminary conditions prior to formal measurement</b> .....                               | <b>10</b>   |
| <b>6.2.3</b>        | <b>Measurements</b> .....   | <b>11</b>   |
| <b>7</b>            | <b>Report</b> .....   | <b>19</b>   |
| <b>7.1</b>          | <b>Test conditions</b> .....  | <b>19</b>   |
| <b>7.2</b>          | <b>Results</b> .....  | <b>19</b>   |
| <b>Bibliography</b> | .....   | <b>21</b>   |