

# DIN EN 14908-1:2014-08 (E)

## Open Data Communication in Building Automation, Controls and Building Management - Control Network Protocol - Part 1: Protocol Stack; English version EN 14908-1:2014

---

<b>Contents</b>		<b>Page</b>
Foreword .....		5
Introduction .....		6
1	Scope .....	7
2	Normative references .....	7
3	Terms and definitions .....	7
4	Symbols and abbreviations .....	9
4.1	Symbols and graphical representations .....	9
4.2	Abbreviations .....	11
5	Overview of protocol layering .....	11
6	MAC sublayer .....	13
6.1	General .....	13
6.2	Service provided .....	13
6.3	Interface to the link layer .....	13
6.4	Interface to the physical layer .....	14
6.5	MPDU format .....	15
6.6	Predictive p-persistent CSMA -- overview description .....	15
6.7	Idle channel detection .....	16
6.8	Randomising .....	17
6.9	Backlog estimation .....	17
6.10	Optional priority .....	18
6.11	Optional collision detection .....	19
6.12	Beta1, Beta2 and Preamble Timings .....	19
7	Link layer .....	21
7.1	Assumptions .....	21
7.2	Service provided .....	22
7.3	CRC .....	22
7.4	Transmit algorithm .....	23
7.5	Receive Algorithm .....	23
8	Network layer .....	23
8.1	Assumptions .....	23
8.2	Service provided .....	25
8.3	Service interface .....	25
8.4	Internal structuring of the network layer .....	26
8.5	NPDU format .....	26
8.6	Address recognition .....	27
8.7	Routers .....	27
8.8	Routing algorithm .....	28
8.9	Learning algorithm -- subnets .....	28
9	Transaction control sublayer .....	28

9.1	Assumptions .....	28
9.2	Service provided .....	29
9.3	Service interface .....	29
9.4	State variables .....	29
9.5	Transaction control algorithm .....	30
10	Transport layer .....	30
10.1	Assumptions .....	30
10.2	Service provided .....	30
10.3	Service interface .....	31
10.4	TPDU types and formats .....	31
10.5	Protocol diagram .....	33
10.6	Transport protocol state variables .....	33
10.7	Send algorithm .....	33
10.8	Receive algorithm .....	34
10.9	Receive transaction record pool size and configuration engineering .....	34
11	Session layer .....	36
11.1	Assumptions .....	36
11.2	Service Provided .....	36
11.3	Service interface .....	37
11.4	Internal structure of the session layer .....	37
11.5	SPDU types and formats .....	38
11.6	Protocol timing diagrams .....	40
11.7	Request-response state variables .....	43
11.8	Request-response protocol -- client part .....	43
11.9	Request-response protocol -- server part .....	43
11.10	Request-response protocol timers .....	44
11.11	Authentication protocol .....	44
11.12	Encryption algorithm .....	44
11.13	Retries and the role of the checksum function .....	44
11.14	Random Number Generation .....	45
11.15	Using Authentication .....	45
12	Presentation/application layer .....	45
12.1	Assumptions .....	45
12.2	Service provided .....	45
12.3	Service interface .....	46
12.4	APDU types and formats .....	47
12.5	Protocol diagrams .....	48
12.6	Application protocol state variables .....	50
12.7	Request - response messaging in offline state .....	50
12.8	Network variables .....	51
12.9	Error notification to the application program .....	52
13	Network management & diagnostics .....	53
13.1	Assumptions .....	53
13.2	Services provided .....	53
13.3	Network management and diagnostics application structure .....	53
13.4	Node states .....	53
13.5	Using the network management services .....	54
13.6	Using router network management commands .....	58
13.7	NMPDU formats and types .....	58
13.8	DPDU types and formats .....	79
Annex A (normative) Reference implementation .....		84
A.1	General .....	84
A.2	Predictive CSMA algorithm .....	84
Annex B (normative) Additional Data Structures .....		376

<b>B.1</b>	<b>General</b> .....	<b>376</b>
<b>B.2</b>	<b>Read-only structures</b> .....	<b>377</b>
<b>B.3</b>	<b>Domain table</b> .....	<b>382</b>
<b>B.4</b>	<b>Address table</b> .....	<b>382</b>
<b>B.5</b>	<b>Network variable tables - informative</b> .....	<b>387</b>
<b>B.6</b>	<b>Self-Identification structures</b> .....	<b>389</b>
<b>B.7</b>	<b>Configuration structure</b> .....	<b>396</b>
<b>B.8</b>	<b>Statistics relative structure</b> .....	<b>398</b>
<b>Annex C (informative) Behavioral characteristics</b> .....		<b>400</b>
<b>C.1</b>	<b>Channel capacity and throughput</b> .....	<b>400</b>
<b>C.2</b>	<b>Network metrics</b> .....	<b>401</b>
<b>C.3</b>	<b>Transaction metrics</b> .....	<b>402</b>
<b>C.4</b>	<b>Boundary conditions -- power-up</b> .....	<b>403</b>
<b>C.5</b>	<b>Boundary conditions -- high load</b> .....	<b>403</b>
<b>Annex D (normative) PDU summary</b> .....		<b>404</b>
<b>Annex E (normative) Naming and addressing</b> .....		<b>406</b>
<b>E.1</b>	<b>Address types and formats</b> .....	<b>406</b>
<b>E.2</b>	<b>Domains</b> .....	<b>406</b>
<b>E.3</b>	<b>Subnets and nodes</b> .....	<b>407</b>
<b>E.4</b>	<b>Groups</b> .....	<b>407</b>
<b>E.5</b>	<b>Unique_Node_ID and node address assignment</b> .....	<b>408</b>
<b>E.6</b>	<b>NPDU addressing</b> .....	<b>408</b>
<b>Bibliography</b> .....		<b>411</b>