

DIN EN 13757-5:2016-02 (E)

Communication systems for meters - Part 5: Wireless M-Bus relaying

| Contents | | Page |
|-----------------|---|-------------|
| | European foreword | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 6 |
| 4 | Symbols | 9 |
| 5 | Introduction | 9 |
| 5.1 | General | 9 |
| 5.2 | Use of retransmission | 9 |
| 5.3 | Repeating | 10 |
| 5.4 | Relaying | 12 |
| 5.4.1 | Overview | 12 |
| 5.4.2 | Use of routers | 15 |
| 5.4.3 | Use of gateways | 15 |
| 5.4.4 | Data duplication | 16 |
| 5.4.5 | Use of power strobed units | 17 |
| 5.4.6 | Error handling | 18 |
| 5.4.7 | Time synchronization | 18 |
| 5.5 | Protocol possibilities | 20 |
| 6 | Mode P, protocol using routers | 20 |
| 6.1 | General | 20 |
| 6.2 | Physical Layer protocol | 20 |
| 6.2.1 | General | 20 |
| 6.2.2 | Transmitter | 21 |
| 6.2.3 | Receiver | 22 |
| 6.3 | Data encoding | 23 |
| 6.3.1 | Manchester encoding | 23 |
| 6.3.2 | Order of transmission of the encoded data | 23 |
| 6.3.3 | Wake up and preamble chip sequences | 23 |
| 6.4 | Data Link Layer protocol | 23 |
| 6.4.1 | General | 23 |
| 6.4.2 | Frame format | 23 |
| 6.4.3 | C-field | 25 |
| 6.4.4 | M- and A-fields | 26 |
| 6.4.5 | The CI-field | 26 |
| 6.4.6 | Message handling | 26 |
| 6.4.7 | Timing requirements | 27 |
| 6.5 | Network Layer protocol | 28 |
| 6.5.1 | General | 28 |
| 6.5.2 | Network Layer format | 28 |
| 6.5.3 | Relaying rules | 29 |
| 6.6 | Application Layer protocol | 30 |
| 6.6.1 | CI-field | 30 |
| 6.6.2 | Error reporting service | 30 |
| 6.6.3 | Network management service | 32 |
| 7 | Mode R2, protocol using gateways | 38 |

| | | |
|-------|--|----|
| 7.1 | General | 38 |
| 8 | Mode Q, protocol supporting precision timing | 38 |
| 8.1 | General | 38 |
| 8.2 | Physical Layer protocol | 38 |
| 8.2.1 | General | 38 |
| 8.2.2 | Transmitter | 38 |
| 8.2.3 | Receiver | 39 |
| 8.3 | Data Encoding | 40 |
| 8.3.1 | NRZ encoding | 40 |
| 8.3.2 | Order of transmission of the encoded data | 40 |
| 8.3.3 | Wake up and preamble bit sequences | 41 |
| 8.4 | Data Link Layer protocol | 41 |
| 8.4.1 | General | 41 |
| 8.4.2 | Frame format | 41 |
| 8.4.3 | Normal Data Link Layer frame handling | 44 |
| 8.4.4 | Search Link Layer frame handling | 45 |
| 8.5 | Mode Q, Network Layer protocol | 47 |
| 8.5.1 | General | 47 |
| 8.5.2 | Network layer format | 47 |
| 8.5.3 | Address conversion rules | 50 |
| 8.5.4 | Routing rules | 50 |
| 8.5.5 | Timing requirements | 53 |
| 8.6 | Mode Q, Application Layer protocol | 54 |
| 8.6.1 | General | 54 |
| 8.6.2 | EN 13757-1 Application Layer | 54 |
| 8.6.3 | Error reporting | 55 |
| 8.6.4 | Alarm reporting | 57 |
| 8.6.5 | Network Management service | 58 |
| 8.6.6 | Timing requirements | 62 |
| 8.6.7 | COSEM extension | 63 |
| 9 | Single-hop repeaters | 64 |
| 9.1 | General | 64 |
| 9.1.1 | Ways of operating | 64 |
| 9.1.2 | Unregistered repetition | 64 |
| 9.1.3 | Registered repetition | 65 |
| 9.1.4 | Assigned repetition | 65 |
| 9.2 | Physical Layer protocol and data encoding | 65 |
| 9.3 | Media Access duty cycle | 66 |
| 9.4 | Timing | 66 |
| 9.4.1 | General | 66 |
| 9.4.2 | Uplink delay - default time slot | 66 |
| 9.4.3 | Uplink delay - optional timeslot | 67 |
| 9.4.4 | Uplink delay - randomly delayed repetition | 67 |
| 9.4.5 | Downlink delay and FAC-Transmission delay | 67 |
| 9.4.6 | Installation announcement delay | 68 |
| 9.4.7 | Other Device response delay | 68 |
| 9.5 | Data Link Layer protocol | 68 |
| 9.5.1 | General | 68 |
| 9.5.2 | C-Field | 68 |
| 9.5.3 | Address | 69 |
| 9.6 | Transport Layer and Extended Link Layer protocol | 69 |
| 9.6.1 | General | 69 |
| 9.6.2 | Hop Count, (H-field) | 69 |
| 9.6.3 | Repeated Access (R-field) | 70 |
| 9.6.4 | Transfer of H- and R-fields within a frame | 70 |
| 9.7 | Application Layer Protocol | 71 |
| 9.7.1 | General | 71 |
| 9.7.2 | Common functions | 71 |
| 9.7.3 | CI field | 72 |
| 9.7.4 | Repeater management data elements | 72 |

| | | |
|--|---|------------|
| 9.8 | Error Reporting Services | 75 |
| 9.8.1 | General | 75 |
| 9.8.2 | Error type | 75 |
| 9.9 | Management Functions | 76 |
| 9.9.1 | General | 76 |
| 9.9.2 | Data elements | 76 |
| 9.9.3 | Meter Management | 78 |
| 9.9.4 | Get List | 81 |
| 9.9.5 | Radio Scan List | 84 |
| 9.9.6 | Repeater Status | 86 |
| Annex A (informative) Timing Diagrams for a Single Hop Repeater | | 89 |
| Annex B (informative) Message examples | | 100 |
| B.1 | Command to Repeater and response | 100 |
| B.1.1 | General | 100 |
| B.1.2 | Configuration | 100 |
| B.1.3 | Detailed data, command | 101 |
| B.1.4 | Detailed data, acknowledge | 102 |
| B.2 | Readout of Radio Scan List | 102 |
| B.2.1 | General | 102 |
| B.2.2 | Configuration | 102 |
| B.2.3 | Detailed data, command | 103 |
| B.2.4 | Detailed data, acknowledge | 104 |
| B.2.5 | Detailed data, request | 105 |
| B.2.6 | Detailed data, response | 106 |
| Bibliography | | 108 |