

DIN EN 1434-1:2016-02 (E)

Heat meters - Part 1: General requirements

| Contents | | Page |
|-------------------------|--|-------------|
| European foreword | | 4 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 6 |
| 4 | Types of instruments | 11 |
| 4.1 | General | 11 |
| 4.2 | Complete instrument | 11 |
| 4.3 | Combined instrument | 11 |
| 4.4 | Hybrid instrument | 11 |
| 4.5 | Sub-assemblies of a heat meter, which is a combined instrument | 11 |
| 4.5.1 | General | 11 |
| 4.5.2 | Flow sensor | 12 |
| 4.5.3 | Temperature sensor pair | 12 |
| 4.5.4 | Calculator | 12 |
| 4.6 | Equipment under test (EUT) | 12 |
| 5 | Rated operating conditions | 12 |
| 5.1 | Limits of temperature range | 12 |
| 5.2 | Limits of temperature differences | 12 |
| 5.3 | Limits of flow rate | 12 |
| 5.4 | Limit of thermal power | 13 |
| 5.5 | Limits of working pressure (PS and Pmin) | 13 |
| 5.6 | Nominal pressure (PN) | 13 |
| 5.7 | Limits in ambient temperature | 13 |
| 5.8 | Limits in deviations in supply voltage | 13 |
| 5.9 | Maximum pressure loss | 13 |
| 5.10 | Specific requirements on registration devices | 13 |
| 5.10.1 | General | 13 |
| 5.10.2 | Suitability | 13 |
| 5.10.3 | Rated operated conditions | 14 |
| 5.10.4 | Indication | 14 |
| 5.10.5 | MPE | 15 |
| 6 | Technical characteristics | 15 |
| 6.1 | Materials and construction | 15 |
| 6.2 | Requirements outside the limiting values of the flow rate | 16 |
| 6.3 | Display | 16 |
| 6.4 | Protection against fraud | 16 |
| 6.5 | Supply voltage | 17 |
| 6.6 | Qualifying immersion depth of a temperature sensor | 17 |
| 6.7 | The influence on a temperature sensor pair caused by mounting in pockets | 17 |
| 6.8 | Reproducibility | 17 |
| 6.9 | Repeatability | 17 |
| 6.10 | Software | 18 |
| 7 | Specified working range | 18 |
| 7.1 | General | 18 |
| 7.2 | Temperature difference | 18 |

| | | |
|-------|--|----|
| 7.3 | Flow rate | 18 |
| 8 | Heat transmission formula | 18 |
| 9 | Metrological characteristics (Maximum Permissible Error, MPE) | 19 |
| 9.1 | General | 19 |
| 9.2 | Values of maximum permissible errors | 19 |
| 9.2.1 | Maximum permissible relative errors of complete heat meters | 19 |
| 9.2.2 | Maximum permissible relative error of sub-assemblies | 19 |
| 9.3 | Application of maximum permissible errors | 20 |
| 10 | Environmental classification | 20 |
| 10.1 | General | 20 |
| 10.2 | Environmental class A (Domestic use, indoor installations) | 21 |
| 10.3 | Environmental class B (Domestic use, outdoor installations) | 21 |
| 10.4 | Environmental class C (Industrial installations) | 21 |
| 10.5 | Mechanical classes M1 to M3 | 21 |
| 11 | Heat meter specification | 21 |
| 11.1 | General | 21 |
| 11.2 | Flow sensor | 21 |
| 11.3 | Temperature sensor pair | 23 |
| 11.4 | Calculator | 23 |
| 11.5 | Complete meters | 25 |
| 12 | Information to be made available by the manufacturer or supplier | 26 |
| 12.1 | Installation instructions | 26 |
| 12.2 | Parameter setting instructions | 27 |
| 12.3 | Adjustment instructions | 28 |
| 12.4 | Maintenance instructions | 28 |
| 12.5 | Hints for disposal instructions | 29 |
| | Annex A (normative) Heat coefficient equations | 30 |
| | Annex B (normative) Flow conditioner package | 32 |
| | Annex C (normative) Fast response meters | 34 |
| | Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2004/22/EC, MID | 35 |
| | Bibliography | 37 |