

# DIN EN 15316-2:2017-09 (E)

## Energy performance of buildings - Method for calculation of system energy requirements and system efficiencies - Part 2: Space emission systems (heating and cooling), Module M3-5, M4-5

---

<b>Contents</b>		<b>Page</b>
European foreword .....		4
Introduction .....		5
1	Scope .....	7
2	Normative references .....	9
3	Terms and definitions .....	9
4	Symbols and abbreviations .....	10
4.1	Symbols .....	10
4.2	Subscripts .....	10
5	Description of the method .....	10
5.1	Output of the method .....	10
5.2	General description of the method .....	11
6	Calculation Method .....	11
6.1	Output data .....	11
6.2	Calculation time steps .....	12
6.3	Input data .....	12
6.4	Monthly and yearly calculation procedure .....	15
6.5	Hourly calculation procedure .....	20
7	Quality control .....	24
8	Compliance check .....	24
Annex A (normative) Template for choices, input data and references (Additional heating and cooling losses / auxiliary energy) .....		25
A.1	Introduction .....	25
A.2	Temperature variation for free heating surfaces (radiators), room heights 4 m (heating case) .....	26
A.3	Temperature Variation for component integrated heating surfaces (panel heaters) (room heights 4 m, heating case) .....	28
A.4	Temperature variation for air heating systems; room heights 4 m (heating case) .....	30
A.5	Temperature Variation for electrical heating (room heights 4 m, heating case) .....	31
A.6	Temperature Variation air heating (ventilation systems, room heights 4 m, heating case) .....	32
A.7	Temperature variation for room spaces with heights > 4 m (large indoor space buildings, heating case) .....	32
A.8	Temperature variation for room heaters fired by solid fuel .....	35
A.9	Temperature variation for water based cooling systems; room heights 4 m (cooling case) .....	36
A.10	Auxiliary Energy .....	37
A.11	Additional Information .....	38

<b>Annex B (informative) Default choices, input data and references (additional heating and cooling losses / auxiliary energy)</b> .....	<b>40</b>
<b>B.1 Introduction</b> .....	<b>40</b>
<b>B.2 Temperature variation for free heating surfaces (radiators); room heights 4 m (heating case)</b> .....	<b>41</b>
<b>B.3 Temperature Variation for component integrated heating surfaces (panel heaters) (room heights 4 m, heating case)</b> .....	<b>43</b>
<b>B.4 Temperature variation for air heating systems; room heights 4 m (heating case)</b> .....	<b>45</b>
<b>B.5 Temperature Variation for electrical heating (room heights 4 m, heating case)</b> .....	<b>46</b>
<b>B.6 Temperature Variation air heating (ventilation systems, room heights 4 m, heating case)</b>	<b>47</b>
<b>B.7 Temperature variation for room spaces with heights &gt; 4 m (large indoor space buildings, heating case)</b> .....	<b>47</b>
<b>B.8 Temperature variation for room heaters fired by solid fuel</b> .....	<b>50</b>
<b>B.9 Temperature variation for water based cooling systems; room heights 4 m (cooling case)</b> .....	<b>51</b>
<b>B.10 Auxiliary Energy</b> .....	<b>52</b>
<b>B.11 Additional Information</b> .....	<b>53</b>
<b>Bibliography</b> .....	<b>55</b>