

DIN EN 15316-5:2017-09 (E)

Energy performance of buildings - Method for calculation of system energy requirements and system efficiencies - Part 5: Space heating and DHW storage systems (not cooling), Module M3-7, M8-7

| Contents | | Page |
|---|---|-------------|
| European foreword | | 5 |
| Introduction | | 6 |
| 1 | Scope | 8 |
| 2 | Normative references | 10 |
| 3 | Terms and definitions | 10 |
| 4 | Symbols and abbreviations | 11 |
| 4.1 | Symbols | 11 |
| 4.2 | Subscripts | 11 |
| 5 | Description of the methods | 11 |
| 5.1 | Output of the method | 11 |
| 5.2 | Extension of the method | 11 |
| 5.3 | Technologies covered and schematisation of the hot water storage system | 12 |
| 5.4 | Principles for hot water storage systems | 13 |
| 6 | Calculation of storage systems | 14 |
| 6.1 | Output data | 14 |
| 6.2 | Calculation time steps | 17 |
| 6.3 | Input data | 17 |
| 6.3.1 | Source of data | 17 |
| 6.3.2 | Product data | 17 |
| 6.3.3 | System design data | 19 |
| 6.3.4 | Control | 19 |
| 6.3.5 | Operating conditions | 19 |
| 6.3.6 | Constants and physical data | 20 |
| 6.4 | Calculation procedure | 21 |
| 6.4.1 | Applicable time-step | 21 |
| 6.4.2 | Operating conditions calculation | 21 |
| 6.4.3 | Energy calculation (storage modelled with multi volumes - Method A) | 21 |
| 6.4.4 | Simplified calculation procedure (storage modelled with a single volume - Method B) | 26 |
| 6.4.5 | Thermal losses | 28 |
| 6.4.6 | Calculation of the auxiliary energy | 28 |
| 6.4.7 | Recoverable, recovered thermal losses | 28 |
| 7 | Quality control | 29 |
| 8 | Compliance check | 29 |
| Annex A (informative) Template for input data and choices | | 31 |
| A.1 | Model information | 31 |
| A.2 | Product description data | 31 |
| A.2.1 | Storage type | 31 |
| A.2.2 | Type of energy use (services) | 31 |

| | | |
|--|--|-----------|
| A.2.3 | Storage fuel | 31 |
| A.2.4 | CE marking | 32 |
| A.2.5 | Dimension | 32 |
| A.2.6 | Energy input/output | 32 |
| A.2.7 | Multiple energy input/output | 33 |
| A.2.8 | Stand-by thermal losses | 33 |
| A.2.9 | Factors for energy recovery | 34 |
| A.3 | Design data | 35 |
| A.3.1 | Localization | 35 |
| A.3.2 | Hydraulic connection | 35 |
| A.3.3 | Storage control type | 35 |
| A.3.3.1 | Type of control | 35 |
| A.3.3.2 | Adaptation of thermal losses for monthly or annual step time | 36 |
| A.4 | Operative conditions for method A - hourly calculation time step | 36 |
| A.5 | Operative conditions for Method B - bin, monthly or annual calculation time step | 37 |
| Annex B (informative) Default Input data | | 38 |
| B.1 | Model information | 38 |
| B.2 | Product description data | 38 |
| B.2.1 | Storage type | 38 |
| B.2.2 | Type of energy use (services) | 38 |
| B.2.3 | Storage fuel | 38 |
| B.2.4 | CE marking | 38 |
| B.2.5 | Dimension | 38 |
| B.2.6 | Energy input/output | 38 |
| B.2.7 | Multiple energy input/output | 39 |
| B.2.8 | Stand-by thermal losses | 39 |
| B.2.9 | Factors for energy recovery | 41 |
| B.3 | Design data | 41 |
| B.3.1 | Localization | 41 |
| B.3.2 | Hydraulic connection | 41 |
| B.3.3 | Storage control type | 41 |
| B.3.3.1 | Type of control | 41 |
| B.3.3.2 | Adaptation of thermal losses for monthly or annual step time | 41 |
| B.4 | Operative conditions for method A - hourly calculation time step | 41 |
| B.5 | Operative conditions for Method B - bin, monthly or annual calculation time step | 42 |
| Annex C (normative) Selection of methods | | 43 |
| C.1 | Method A - Model based on a representation of stratified temperature in the storage | 43 |
| C.1.1 | Applicability of the stratified model | 43 |
| C.1.2 | Selection of the number of volumes to model the storage unit | 43 |
| C.2 | Method B - Model based on a representation of an homogenous temperature in the storage | 43 |
| Annex D (informative) Alternative presentation for Method A | | 44 |
| D.1 | Step 2 - Direct withdrawal of a heat quantity (volume to withdraw) | 44 |
| D.1.1 | General | 44 |
| D.1.2 | Additional | 46 |
| D.2 | Step 3 - Temperature of the storage after volume withdrawal | 46 |
| D.3 | Step 6 - indirect heat input and output | 47 |
| D.4 | Rearrange temperatures in the storage to a natural state | 49 |
| D.5 | Heat exchanger - additional | 50 |
| D.5.1 | General | 50 |
| D.5.2 | Indirect heat input in the storage, using a solar collector loop | 50 |
| D.5.3 | Indirect heat output from the storage to the space heating service | 51 |
| Bibliography | | 52 |