DIN EN 15316-5:2017-09 (E)

Energy performance of buildings - Method for ca lculation of system energy requirements and system efficiencies - Part 5: Space heating and DHW storage systems (not cooling), Module M3-7, M8-7

Contents

Page

European foreword 5

Introduction 6

1 Scope 8

2 Normative references 10

3 Terms and definitions 10

4 Symbols and abbreviations 11
4.1 Symbols 11
4.2 Subscripts 11

5 Description of the methods 11
5.1 Output of the method 11
5.2 Extension of the method 11
5.3 Technologies covered and schematisation of the hot water storage system 12
5.4 Principles for hot water storage systems 13

6 Calculation of storage systems 14
6.1 Output data 14
6.2 Calculation time steps 17
6.3 Input data 17
6.3.1 Source of data 17
6.3.2 Product data 17
6.3.3 System design data 19
6.3.4 Control 19
6.3.5 Operating conditions 19
6.3.6 Constants and physical data 20
6.4 Calculation procedure 21
6.4.1 Applicable time-step 21
6.4.2 Operating conditions calculation 21
6.4.3 Energy calculation (storage modelled with multi volumes - Method A) 21
6.4.4 Simplified calculation procedure (storage modelled with a single volume - Method B) 26
6.4.5 Thermal losses 28
6.4.6 Calculation of the auxiliary energy 28
6.4.7 Recoverable, recovered thermal losses 28

7 Quality control 29

8 Compliance check 29

Annex A (informative) Template for input data and choices 31

A.1 Model information 31
A.2 Product description data 31
A.2.1 Storage type 31
A.2.2 Type of energy use (services) 31

A.2.3 Storage fuel ... 31
A.2.4 CE marking ... 32
A.2.5 Dimension ... 32
A.2.6 Energy input/output ... 32
A.2.7 Multiple energy input/output ... 33
A.2.8 Stand-by thermal losses ... 33
A.2.9 Factors for energy recovery ... 34
A.3 Design data ... 35
A.3.1 Localization ... 35
A.3.2 Hydraulic connection ... 35
A.3.3 Storage control type ... 35
A.3.3.1 Type of control ... 35
A.3.3.2 Adaptation of thermal losses for monthly or annual step time ... 36
A.4 Operative conditions for method A - hourly calculation time step ... 36
A.5 Operative conditions for Method B - bin, monthly or annual calculation time step ... 37

Annex B (informative) Default Input data ... 38

B.1 Model information ... 38
B.2 Product description data ... 38
B.2.1 Storage type ... 38
B.2.2 Type of energy use (services) ... 38
B.2.3 Storage fuel ... 38
B.2.4 CE marking ... 38
B.2.5 Dimension ... 38
B.2.6 Energy input/output ... 38
B.2.7 Multiple energy input/output ... 39
B.2.8 Stand-by thermal losses ... 39
B.2.9 Factors for energy recovery ... 41
B.3 Design data ... 41
B.3.1 Localization ... 41
B.3.2 Hydraulic connection ... 41
B.3.3 Storage control type ... 41
B.3.3.1 Type of control ... 41
B.3.3.2 Adaptation of thermal losses for monthly or annual step time ... 41
B.4 Operative conditions for method A - hourly calculation time step ... 41
B.5 Operative conditions for Method B - bin, monthly or annual calculation time step ... 42

Annex C (normative) Selection of methods ... 43

C.1 Method A - Model based on a representation of stratified temperature in the storage ... 43
C.1.1 Applicability of the stratified model ... 43
C.1.2 Selection of the number of volumes to model the storage unit ... 43
C.2 Method B - Model based on a representation of an homogenous temperature in the storage ` ... 43

Annex D (informative) Alternative presentation for Method A ... 44

D.1 Step 2 - Direct withdrawal of a heat quantity (volume to withdraw) ... 44
D.1.1 General ... 44
D.1.2 Additional ... 46
D.2 Step 3 - Temperature of the storage after volume withdrawal ... 46
D.3 Step 6 - indirect heat input and output ... 47
D.4 Rearrange temperatures in the storage to a natural state ... 49
D.5 Heat exchanger - additional ... 50
D.5.1 General ... 50
D.5.2 Indirect heat input in the storage, using a solar collector loop ... 50
D.5.3 Indirect heat output from the storage to the space heating service ... 51

Bibliography ... 52