

# DIN EN 12831-1:2017-09 (E)

## Energy performance of buildings - Method for calculation of the design heat load - Part 1: Space heating load, Module M3-3

---

<b>Contents</b>		<b>Page</b>
European foreword .....		5
Introduction .....		6
1	Scope .....	8
2	Normative references .....	12
3	Terms and definitions .....	12
4	Symbols and abbreviations .....	15
4.1	Symbols .....	15
4.2	Subscripts .....	16
5	Description of the methods .....	19
6	Standard method - Heat load of rooms, building entities and buildings .....	20
6.1	Output data .....	20
6.2	Input data .....	21
6.3	Calculation procedure .....	27
6.3.1	Design heat load .....	27
6.3.2	Design transmission heat losses of a heated space (i) .....	29
6.3.3	Design ventilation heat loss .....	33
6.3.4	Additional heating-up power in intermittently heated spaces .....	41
6.3.5	Time constant .....	42
6.3.6	Heat transfer coefficients without temperature adjustment .....	43
6.3.7	External design temperature (climatic data) .....	44
6.3.8	Influence of the heat emission system in high rooms (ceiling height 4 m) .....	46
7	Simplified method for the calculation of the design heat load of a heated space (single rooms) .....	48
7.1	Output data .....	48
7.2	Input data .....	48
7.3	Calculation procedure .....	49
7.3.1	Design heat load of a heated space .....	49
7.3.2	Design transmission heat loss of a heated space .....	50
7.3.3	Design ventilation heat loss of a heated space .....	50
8	Simplified method for the calculation of the building design heat load .....	51
8.1	Output data .....	51
8.2	Input data .....	51
8.3	Calculation procedure .....	52
8.3.1	Building design heat load .....	52
8.3.2	Building design transmission heat loss .....	53
8.3.3	Design ventilation heat loss of a building .....	53
9	Compliance check .....	54
9.1	General .....	54
9.2	Dimensioning of heat emission systems .....	54
9.3	Dimensioning of heat generators .....	54

<b>Annex A (normative) Input data, structure for default values</b>	<b>55</b>
<b>A.1 General</b>	<b>55</b>
<b>A.2 Input data for the standard method (6)</b>	<b>55</b>
<b>A.2.1 Consideration of thermal bridges</b>	<b>55</b>
<b>A.2.2 Correction of U-values for the influence of building element properties and meteorological conditions</b>	<b>55</b>
<b>A.2.3 Heat loss through the ground</b>	<b>55</b>
<b>A.2.4 Temperature adjustment for heat loss to unheated spaces</b>	<b>56</b>
<b>A.2.5 Internal temperatures of adjacent building entities</b>	<b>56</b>
<b>A.2.6 Influence of the heat emission system in high rooms</b>	<b>56</b>
<b>A.2.7 Specific thermal storage capacity <math>c_{eff}</math></b>	<b>57</b>
<b>A.2.8 Specific properties of air</b>	<b>57</b>
<b>A.2.9 Volume flow ratio between room (i) and zone (z)</b>	<b>58</b>
<b>A.2.10 Air tightness</b>	<b>58</b>
<b>A.2.11 Minimum air change rate</b>	<b>58</b>
<b>A.2.12 Coefficient for the volume flow ratio <math>f_{qv,z}</math></b>	<b>59</b>
<b>A.2.13 Estimation of design data of external ATDs</b>	<b>59</b>
<b>A.2.14 Pressure exponent for leakages</b>	<b>59</b>
<b>A.2.15 Adjustment factor for the orientation of the zone (orientation factor)</b>	<b>59</b>
<b>A.2.16 Adjustment factor for the number of exposed facades</b>	<b>60</b>
<b>A.2.17 Air volume flow through large openings</b>	<b>60</b>
<b>A.2.18 Additional heating-up power in intermittently heated spaces <math>h_u</math></b>	<b>60</b>
<b>A.2.19 Heat gains gain</b>	<b>60</b>
<b>A.3 Input data for the simplified methods (7, 8)</b>	<b>60</b>
<b>A.3.1 Ratio between external and internal surface areas</b>	<b>60</b>
<b>A.3.2 Thermal bridges</b>	<b>61</b>
<b>A.3.3 Temperature correction factor <math>f_x</math></b>	<b>61</b>
<b>A.3.4 Air change rate</b>	<b>61</b>
<b>A.4 Input data for the standard method and the simplified methods</b>	<b>61</b>
<b>A.4.1 Climatic data</b>	<b>61</b>
<b>A.4.2 Internal design temperature</b>	<b>64</b>
<b>A.4.3 Simplified determination of U-Values</b>	<b>64</b>
<b>Annex B (informative) Input data, default values</b>	<b>65</b>
<b>B.1 General</b>	<b>65</b>
<b>B.2 Input data for the standard method (6)</b>	<b>65</b>
<b>B.2.1 Consideration of thermal bridges</b>	<b>65</b>
<b>B.2.2 Correction of U-values for the influence of building element properties and meteorological conditions</b>	<b>65</b>
<b>B.2.3 Heat loss through the ground</b>	<b>65</b>
<b>B.2.4 Temperature adjustment for heat loss to unheated spaces</b>	<b>66</b>
<b>B.2.5 Internal temperatures of adjacent building entities</b>	<b>66</b>
<b>B.2.6 Influence of the heat emission system in high rooms</b>	<b>66</b>
<b>B.2.7 Specific thermal storage capacity <math>c_{eff}</math></b>	<b>67</b>
<b>B.2.8 Specific properties of air</b>	<b>68</b>
<b>B.2.9 Volume flow ratio between room (i) and zone (z)</b>	<b>68</b>
<b>B.2.10 Air tightness</b>	<b>68</b>
<b>B.2.11 Coefficient for the volume flow ratio <math>f_{qv,z}</math></b>	<b>69</b>
<b>B.2.12 Estimation of design data of external ATDs</b>	<b>70</b>
<b>B.2.13 Pressure exponent for leakages</b>	<b>71</b>
<b>B.2.14 Adjustment factor for the orientation of the zone (orientation factor)</b>	<b>71</b>
<b>B.2.15 Adjustment factor for the number of exposed facades</b>	<b>71</b>
<b>B.2.16 Air volume flow through large openings</b>	<b>71</b>
<b>B.2.17 Additional heating-up power in intermittently heated spaces <math>h_u</math></b>	<b>71</b>
<b>B.2.18 Heat gains gain</b>	<b>71</b>
<b>B.3 Input data for the simplified methods (7, 8)</b>	<b>71</b>
<b>B.3.1 Ratio between external and internal surface areas</b>	<b>71</b>
<b>B.3.2 Thermal bridges</b>	<b>72</b>
<b>B.3.3 Temperature correction factor <math>f_x</math></b>	<b>72</b>
<b>B.3.4 Air change rate</b>	<b>72</b>

<b>B.4</b>	<b>Input data for the standard method and the simplified methods .....</b>	<b>72</b>
<b>B.4.1</b>	<b>Climatic data .....</b>	<b>72</b>
<b>B.4.2</b>	<b>Internal design temperature .....</b>	<b>73</b>
<b>B.4.3</b>	<b>Simplified determination of U-Values .....</b>	<b>74</b>
<b>Annex C (informative) Detailed consideration of thermal bridges .....</b>		<b>77</b>
<b>Annex D (informative) Internal temperatures <math>t_i</math> of adjacent building entities or adjacent unheated spaces within the same building .....</b>		<b>78</b>
<b>Annex E (informative) Equivalent thermal transmittance of building elements against ground .....</b>		<b>81</b>
<b>Annex F (informative) Estimation of heating-up power in intermittently heated spaces (6.3.4) .....</b>		<b>84</b>
<b>F.1</b>	<b>General .....</b>	<b>84</b>
<b>F.2</b>	<b>Determination of the specific heating-up power <math>h_{u,i}</math> based on the time of disuse .....</b>	<b>86</b>
<b>F.3</b>	<b>Determination of the specific heating-up power <math>h_{u,i}</math> based on the internal temperature drop during setback .....</b>	<b>87</b>
<b>Annex G (informative) External air volume flow through large openings .....</b>		<b>89</b>
<b>Bibliography .....</b>		<b>94</b>