

# DIN EN 12831-1:2017-09 (E)

## Energy performance of buildings - Method for calculation of the design heat load - Part 1: Space heating load, Module M3-3

---

| <b>Contents</b>         |   | <b>Page</b> |
|-------------------------|---|-------------|
| European foreword ..... |   | 5           |
| Introduction .....      |   | 6           |
| <b>1</b>                | <b>Scope .....</b>  | <b>8</b>    |
| <b>2</b>                | <b>Normative references .....</b>   | <b>12</b>   |
| <b>3</b>                | <b>Terms and definitions .....</b>  | <b>12</b>   |
| <b>4</b>                | <b>Symbols and abbreviations .....</b>  | <b>15</b>   |
| 4.1                     | Symbols .....   | 15          |
| 4.2                     | Subscripts .....  | 16          |
| <b>5</b>                | <b>Description of the methods .....</b>   | <b>19</b>   |
| <b>6</b>                | <b>Standard method - Heat load of rooms, building entities and buildings .....</b>                          | <b>20</b>   |
| 6.1                     | Output data .....   | 20          |
| 6.2                     | Input data .....  | 21          |
| 6.3                     | Calculation procedure .....   | 27          |
| 6.3.1                   | Design heat load .....  | 27          |
| 6.3.2                   | Design transmission heat losses of a heated space (i) .....   | 29          |
| 6.3.3                   | Design ventilation heat loss .....  | 33          |
| 6.3.4                   | Additional heating-up power in intermittently heated spaces .....   | 41          |
| 6.3.5                   | Time constant .....   | 42          |
| 6.3.6                   | Heat transfer coefficients without temperature adjustment .....   | 43          |
| 6.3.7                   | External design temperature (climatic data) .....   | 44          |
| 6.3.8                   | Influence of the heat emission system in high rooms (ceiling height 4 m) .....                              | 46          |
| <b>7</b>                | <b>Simplified method for the calculation of the design heat load of a heated space (single rooms) .....</b> | <b>48</b>   |
| 7.1                     | Output data .....   | 48          |
| 7.2                     | Input data .....  | 48          |
| 7.3                     | Calculation procedure .....   | 49          |
| 7.3.1                   | Design heat load of a heated space .....  | 49          |
| 7.3.2                   | Design transmission heat loss of a heated space .....   | 50          |
| 7.3.3                   | Design ventilation heat loss of a heated space .....  | 50          |
| <b>8</b>                | <b>Simplified method for the calculation of the building design heat load .....</b>                         | <b>51</b>   |
| 8.1                     | Output data .....   | 51          |
| 8.2                     | Input data .....  | 51          |
| 8.3                     | Calculation procedure .....   | 52          |
| 8.3.1                   | Building design heat load .....   | 52          |
| 8.3.2                   | Building design transmission heat loss .....  | 53          |
| 8.3.3                   | Design ventilation heat loss of a building .....  | 53          |
| <b>9</b>                | <b>Compliance check .....</b>   | <b>54</b>   |
| 9.1                     | General .....   | 54          |
| 9.2                     | Dimensioning of heat emission systems .....   | 54          |
| 9.3                     | Dimensioning of heat generators .....   | 54          |

|  |           |
|--|-----------|
| <b>Annex A (normative) Input data, structure for default values</b> .....  | <b>55</b> |
| <b>A.1 General</b> .....   | <b>55</b> |
| <b>A.2 Input data for the standard method (6)</b> .....  | <b>55</b> |
| <b>A.2.1 Consideration of thermal bridges</b> .....  | <b>55</b> |
| <b>A.2.2 Correction of U-values for the influence of building element properties and meteorological conditions</b> ..... | <b>55</b> |
| <b>A.2.3 Heat loss through the ground</b> .....  | <b>55</b> |
| <b>A.2.4 Temperature adjustment for heat loss to unheated spaces</b> .....   | <b>56</b> |
| <b>A.2.5 Internal temperatures of adjacent building entities</b> .....   | <b>56</b> |
| <b>A.2.6 Influence of the heat emission system in high rooms</b> .....   | <b>56</b> |
| <b>A.2.7 Specific thermal storage capacity <math>c_{eff}</math></b> .....  | <b>57</b> |
| <b>A.2.8 Specific properties of air</b> .....  | <b>57</b> |
| <b>A.2.9 Volume flow ratio between room (i) and zone (z)</b> .....   | <b>58</b> |
| <b>A.2.10 Air tightness</b> .....  | <b>58</b> |
| <b>A.2.11 Minimum air change rate</b> .....  | <b>58</b> |
| <b>A.2.12 Coefficient for the volume flow ratio <math>f_{qv,z}</math></b> .....  | <b>59</b> |
| <b>A.2.13 Estimation of design data of external ATDs</b> .....   | <b>59</b> |
| <b>A.2.14 Pressure exponent for leakages</b> .....   | <b>59</b> |
| <b>A.2.15 Adjustment factor for the orientation of the zone (orientation factor)</b> .....                               | <b>59</b> |
| <b>A.2.16 Adjustment factor for the number of exposed facades</b> .....  | <b>60</b> |
| <b>A.2.17 Air volume flow through large openings</b> .....   | <b>60</b> |
| <b>A.2.18 Additional heating-up power in intermittently heated spaces <math>h_u</math></b> .....                         | <b>60</b> |
| <b>A.2.19 Heat gains gain</b> .....  | <b>60</b> |
| <b>A.3 Input data for the simplified methods (7, 8)</b> .....  | <b>60</b> |
| <b>A.3.1 Ratio between external and internal surface areas</b> .....   | <b>60</b> |
| <b>A.3.2 Thermal bridges</b> .....   | <b>61</b> |
| <b>A.3.3 Temperature correction factor <math>f_x</math></b> .....  | <b>61</b> |
| <b>A.3.4 Air change rate</b> .....   | <b>61</b> |
| <b>A.4 Input data for the standard method and the simplified methods</b> .....   | <b>61</b> |
| <b>A.4.1 Climatic data</b> .....   | <b>61</b> |
| <b>A.4.2 Internal design temperature</b> .....   | <b>64</b> |
| <b>A.4.3 Simplified determination of U-Values</b> .....  | <b>64</b> |
| <b>Annex B (informative) Input data, default values</b> .....  | <b>65</b> |
| <b>B.1 General</b> .....   | <b>65</b> |
| <b>B.2 Input data for the standard method (6)</b> .....  | <b>65</b> |
| <b>B.2.1 Consideration of thermal bridges</b> .....  | <b>65</b> |
| <b>B.2.2 Correction of U-values for the influence of building element properties and meteorological conditions</b> ..... | <b>65</b> |
| <b>B.2.3 Heat loss through the ground</b> .....  | <b>65</b> |
| <b>B.2.4 Temperature adjustment for heat loss to unheated spaces</b> .....   | <b>66</b> |
| <b>B.2.5 Internal temperatures of adjacent building entities</b> .....   | <b>66</b> |
| <b>B.2.6 Influence of the heat emission system in high rooms</b> .....   | <b>66</b> |
| <b>B.2.7 Specific thermal storage capacity <math>c_{eff}</math></b> .....  | <b>67</b> |
| <b>B.2.8 Specific properties of air</b> .....  | <b>68</b> |
| <b>B.2.9 Volume flow ratio between room (i) and zone (z)</b> .....   | <b>68</b> |
| <b>B.2.10 Air tightness</b> .....  | <b>68</b> |
| <b>B.2.11 Coefficient for the volume flow ratio <math>f_{qv,z}</math></b> .....  | <b>69</b> |
| <b>B.2.12 Estimation of design data of external ATDs</b> .....   | <b>70</b> |
| <b>B.2.13 Pressure exponent for leakages</b> .....   | <b>71</b> |
| <b>B.2.14 Adjustment factor for the orientation of the zone (orientation factor)</b> .....                               | <b>71</b> |
| <b>B.2.15 Adjustment factor for the number of exposed facades</b> .....  | <b>71</b> |
| <b>B.2.16 Air volume flow through large openings</b> .....   | <b>71</b> |
| <b>B.2.17 Additional heating-up power in intermittently heated spaces <math>h_u</math></b> .....                         | <b>71</b> |
| <b>B.2.18 Heat gains gain</b> .....  | <b>71</b> |
| <b>B.3 Input data for the simplified methods (7, 8)</b> .....  | <b>71</b> |
| <b>B.3.1 Ratio between external and internal surface areas</b> .....   | <b>71</b> |
| <b>B.3.2 Thermal bridges</b> .....   | <b>72</b> |
| <b>B.3.3 Temperature correction factor <math>f_x</math></b> .....  | <b>72</b> |
| <b>B.3.4 Air change rate</b> .....   | <b>72</b> |

|  |  |           |
|--|--|-----------|
| <b>B.4</b>   | <b>Input data for the standard method and the simplified methods .....</b>   | <b>72</b> |
| <b>B.4.1</b>   | <b>Climatic data .....</b>   | <b>72</b> |
| <b>B.4.2</b>   | <b>Internal design temperature .....</b>   | <b>73</b> |
| <b>B.4.3</b>   | <b>Simplified determination of U-Values .....</b>  | <b>74</b> |
| <b>Annex C (informative) Detailed consideration of thermal bridges .....</b>   |  | <b>77</b> |
| <b>Annex D (informative) Internal temperatures <math>t_{i}</math> of adjacent building entities or adjacent unheated spaces within the same building .....</b> |  | <b>78</b> |
| <b>Annex E (informative) Equivalent thermal transmittance of building elements against ground .....</b>  |  | <b>81</b> |
| <b>Annex F (informative) Estimation of heating-up power in intermittently heated spaces (6.3.4) .....</b>  |  | <b>84</b> |
| <b>F.1</b>   | <b>General .....</b>   | <b>84</b> |
| <b>F.2</b>   | <b>Determination of the specific heating-up power <math>h_{u,i}</math> based on the time of disuse .....</b>                           | <b>86</b> |
| <b>F.3</b>   | <b>Determination of the specific heating-up power <math>h_{u,i}</math> based on the internal temperature drop during setback .....</b> | <b>87</b> |
| <b>Annex G (informative) External air volume flow through large openings .....</b>   |  | <b>89</b> |
| <b>Bibliography .....</b>  |  | <b>94</b> |