

DIN EN 12831-1:2017-09 (E)

Energy performance of buildings - Method for calculation of the design heat load - Part 1: Space heating load, Module M3-3

Contents		Page
European foreword		5
Introduction		6
1	Scope	8
2	Normative references	12
3	Terms and definitions	12
4	Symbols and abbreviations	15
4.1	Symbols	15
4.2	Subscripts	16
5	Description of the methods	19
6	Standard method - Heat load of rooms, building entities and buildings	20
6.1	Output data	20
6.2	Input data	21
6.3	Calculation procedure	27
6.3.1	Design heat load	27
6.3.2	Design transmission heat losses of a heated space (i)	29
6.3.3	Design ventilation heat loss	33
6.3.4	Additional heating-up power in intermittently heated spaces	41
6.3.5	Time constant	42
6.3.6	Heat transfer coefficients without temperature adjustment	43
6.3.7	External design temperature (climatic data)	44
6.3.8	Influence of the heat emission system in high rooms (ceiling height 4 m)	46
7	Simplified method for the calculation of the design heat load of a heated space (single rooms)	48
7.1	Output data	48
7.2	Input data	48
7.3	Calculation procedure	49
7.3.1	Design heat load of a heated space	49
7.3.2	Design transmission heat loss of a heated space	50
7.3.3	Design ventilation heat loss of a heated space	50
8	Simplified method for the calculation of the building design heat load	51
8.1	Output data	51
8.2	Input data	51
8.3	Calculation procedure	52
8.3.1	Building design heat load	52
8.3.2	Building design transmission heat loss	53
8.3.3	Design ventilation heat loss of a building	53
9	Compliance check	54
9.1	General	54
9.2	Dimensioning of heat emission systems	54
9.3	Dimensioning of heat generators	54

Annex A (normative) Input data, structure for default values	55
A.1 General	55
A.2 Input data for the standard method (6)	55
A.2.1 Consideration of thermal bridges	55
A.2.2 Correction of U-values for the influence of building element properties and meteorological conditions	55
A.2.3 Heat loss through the ground	55
A.2.4 Temperature adjustment for heat loss to unheated spaces	56
A.2.5 Internal temperatures of adjacent building entities	56
A.2.6 Influence of the heat emission system in high rooms	56
A.2.7 Specific thermal storage capacity c_{eff}	57
A.2.8 Specific properties of air	57
A.2.9 Volume flow ratio between room (i) and zone (z)	58
A.2.10 Air tightness	58
A.2.11 Minimum air change rate	58
A.2.12 Coefficient for the volume flow ratio $f_{qv,z}$	59
A.2.13 Estimation of design data of external ATDs	59
A.2.14 Pressure exponent for leakages	59
A.2.15 Adjustment factor for the orientation of the zone (orientation factor)	59
A.2.16 Adjustment factor for the number of exposed facades	60
A.2.17 Air volume flow through large openings	60
A.2.18 Additional heating-up power in intermittently heated spaces h_u	60
A.2.19 Heat gains gain	60
A.3 Input data for the simplified methods (7, 8)	60
A.3.1 Ratio between external and internal surface areas	60
A.3.2 Thermal bridges	61
A.3.3 Temperature correction factor f_x	61
A.3.4 Air change rate	61
A.4 Input data for the standard method and the simplified methods	61
A.4.1 Climatic data	61
A.4.2 Internal design temperature	64
A.4.3 Simplified determination of U-Values	64
Annex B (informative) Input data, default values	65
B.1 General	65
B.2 Input data for the standard method (6)	65
B.2.1 Consideration of thermal bridges	65
B.2.2 Correction of U-values for the influence of building element properties and meteorological conditions	65
B.2.3 Heat loss through the ground	65
B.2.4 Temperature adjustment for heat loss to unheated spaces	66
B.2.5 Internal temperatures of adjacent building entities	66
B.2.6 Influence of the heat emission system in high rooms	66
B.2.7 Specific thermal storage capacity c_{eff}	67
B.2.8 Specific properties of air	68
B.2.9 Volume flow ratio between room (i) and zone (z)	68
B.2.10 Air tightness	68
B.2.11 Coefficient for the volume flow ratio $f_{qv,z}$	69
B.2.12 Estimation of design data of external ATDs	70
B.2.13 Pressure exponent for leakages	71
B.2.14 Adjustment factor for the orientation of the zone (orientation factor)	71
B.2.15 Adjustment factor for the number of exposed facades	71
B.2.16 Air volume flow through large openings	71
B.2.17 Additional heating-up power in intermittently heated spaces h_u	71
B.2.18 Heat gains gain	71
B.3 Input data for the simplified methods (7, 8)	71
B.3.1 Ratio between external and internal surface areas	71
B.3.2 Thermal bridges	72
B.3.3 Temperature correction factor f_x	72
B.3.4 Air change rate	72

B.4	Input data for the standard method and the simplified methods	72
B.4.1	Climatic data	72
B.4.2	Internal design temperature	73
B.4.3	Simplified determination of U-Values	74
Annex C (informative) Detailed consideration of thermal bridges		77
Annex D (informative) Internal temperatures t_{i} of adjacent building entities or adjacent unheated spaces within the same building		78
Annex E (informative) Equivalent thermal transmittance of building elements against ground		81
Annex F (informative) Estimation of heating-up power in intermittently heated spaces (6.3.4)		84
F.1	General	84
F.2	Determination of the specific heating-up power $h_{u,i}$ based on the time of disuse	86
F.3	Determination of the specific heating-up power $h_{u,i}$ based on the internal temperature drop during setback	87
Annex G (informative) External air volume flow through large openings		89
Bibliography		94