

ISO 23551-2:2018 (E)

Safety and control devices for gas burners and gas-burning appliances — Particular requirements — Part 2: Pressure regulators

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
3.1	Pressure regulators
3.2	Pressures
3.3	Flow rates
3.4	Component parts
3.5	Performance
4	Classification
4.1	Classes of control
4.2	Groups of controls
4.3	Types of DC supplied controls
5	Test conditions
6	Construction
6.1	General
6.2	Construction requirements
6.2.1	Appearance
6.2.2	Holes
6.2.3	Breather holes
6.2.4	Vent limiters
6.2.5	Screwed fastenings
6.2.6	Moving parts
6.2.7	Sealing caps
6.2.8	Disassembling and assembling for servicing and/or adjustment
6.2.9	Auxiliary channels and orifices
6.2.10	Pre-setting device
6.2.11	Adjustments
6.2.12	Resistance to pressure
6.2.13	Blockage of canals and orifices
6.2.14	Signal tube connections
6.3	Materials
6.3.1	General material requirements
6.3.2	Housing
6.3.2.1	General
6.3.2.2	Requirements
6.3.2.3	Test
6.3.3	Springs providing closing force and sealing force
6.3.4	Resistance to corrosion and surface protection
6.3.5	Impregnation
6.3.6	Seals for glands for moving parts
6.3.7	Jointing
6.4	Connections
6.4.1	General
6.4.2	Connection sizes

6.4.3	Connection types
6.4.4	Threads
6.4.5	Union joints
6.4.6	Flanges
6.4.7	Compression fittings
6.4.8	Flare connections
6.4.9	Nipples for pressure test
6.4.10	Strainers
6.4.10.1	General
6.4.10.2	Requirements
6.4.10.3	Test
6.4.11	Gas connections by GQC
6.5	Gas controls employing electrical components in the gas way
7	Performance
7.1	General
7.2	Leak-tightness
7.2.1	General
7.2.2	Requirements
7.2.3	Test
7.2.3.1	General
7.2.3.2	Test for external leak-tightness
7.2.3.3	Test for internal leak-tightness of controls
7.3	Torsion and bending
7.4	Rated flow rate
7.4.1	General
7.4.2	Requirements
7.4.3	Test
7.4.3.1	Apparatus
7.4.3.2	Test procedure
7.4.3.3	Conversion of air flow rate
7.5	Durability
7.6	Functional requirements
7.7	Endurance
7.8	Vibration test
7.9	Putting the regulator out of action
7.9.1	Requirement
7.9.2	Test putting the regulator out of action
7.10	Endurance
7.11	Lock-up pressure
7.11.1	Requirement
7.11.2	Lock-up pressure test
7.12	Optional EP-rating
7.12.1	General
7.12.2	External leakage resistance
7.12.2.1	Requirement
7.12.2.2	Test
7.12.3	Internal flow resistance
7.12.3.1	Requirement
7.12.3.2	Test
8	Electrical requirements
9	Electromagnetic compatibility (EMC)
10	Marking, installation and operating instructions
10.1	Marking
10.2	Installation and operating instructions
10.3	Warning notice
Annex A	(informative) Leak-tightness test — Volumetric method
Annex B	(informative) Leak-tightness test — Pressure-loss method

- Annex C** (normative) Conversion of pressure loss into leakage rate
- Annex D** (normative) Gas quick connector (GQC)
- Annex E** (normative) Elastomers/requirements resistance to lubricants and gas
- Annex F** (normative) Specific regional requirements in European countries
- Annex G** (normative) Specific regional requirements in Canada and USA
- Annex H** (normative) Specific regional requirements in Japan
- Annex I** (informative) Regulator application examples
- Annex J** (normative) Functional requirements and regulator performance testing — Method A
 - J.1 General
 - J.2 General test procedure
 - J.2.1 General
 - J.2.2 Apparatus
 - J.2.3 Conversion of the air flow rate
 - J.2.4 Methods of test
 - J.2.5 Class A pressure regulator performance
 - J.2.5.1 Requirement
 - J.2.5.2 Test
 - J.2.6 Class B pressure regulator performance
 - J.2.6.1 Requirement
 - J.2.6.2 Test
 - J.2.7 Class C pressure regulator performance
 - J.2.7.1 Requirement
 - J.2.7.2 Test
 - J.2.8 Class D pressure regulator performance
 - J.2.8.1 Requirement
 - J.2.8.2 Test
 - J.2.9 Pressure drop
 - J.2.10 Endurance
 - J.2.10.1 Requirement
 - J.2.10.2 Test
 - J.2.10.2.1 Regulator Classes A, B and C and ratio regulators — Cycling and temperature
 - J.2.10.2.2 Regulators Class D Cycling and Temperature
 - J.3 Summary of requirements and test procedures
 - J.3.1 Requirements
 - J.3.2 Test procedure
- Annex K** (normative) Functional requirements and regulator performance testing — Method B
 - K.1 Requirements
 - K.1.1 Mounting regulator for test
 - K.1.2 Outlet pressure range
 - K.1.3 Range of regulation capacity
 - K.1.4 Regulators designated to operate at pilot flow rate
 - K.1.5 Integrity of operation
 - K.1.6 Endurance
 - K.2 Test
 - K.2.1 General test procedures
 - K.2.2 Outlet pressure range
 - K.2.2.1 General
 - K.2.2.2 Non-adjustable regulator
 - K.2.2.3 Convertible regulator
 - K.2.2.4 Adjustable regulator
 - K.2.3 Range of regulation capacity
 - K.2.3.1 Non-adjustable regulator
 - K.2.3.2 Convertible regulator
 - K.2.3.3 Adjustable regulator
 - K.2.3.4 Multi-stage regulator

- K.2.4** Regulators designated to operate at pilot flow rate
- K.2.4.1** General
- K.2.4.2** Regulation capacity
- K.2.4.3** Pressure variation
- K.2.5** Integrity of operation
- K.2.5.1** Creating base curve
- K.2.6** Endurance

Annex L (normative) Pneumatic gas/air ratio pressure regulator performance

- L.1** General
- L.2** General test procedure
- L.2.1** Apparatus
- L.2.2** Conversion of the air flow rate
- L.2.3** Control performance and stability
- L.2.3.1** Control performance requirement
- L.2.3.1.1** General
- L.2.3.1.2** Control pressure variation with signal pressure
- L.2.3.1.3** Control pressure variation with load determining pressure
- L.2.3.2** Stability requirement
- L.2.3.3** Test
- L.2.3.3.1** General
- L.2.3.3.2** Control pressure variation with signal pressure
- L.2.3.3.3** Control pressure variation with load determining pressure
- L.2.3.3.4** Flow variation pneumatic gas/air ratio regulator industrial type
- L.2.3.3.5** Flow variation zero pressure regulator industrial type
- L.2.4** Settling time test
- L.2.4.1** Requirement
- L.2.4.2** Test
- L.2.5** Gas/air ratio adjustment
- L.2.5.1** Requirement
- L.2.5.2** Test
- L.2.6** Offset adjustment
- L.2.6.1** Requirement
- L.2.6.2** Test
- L.2.7** Endurance
- L.2.7.1** Requirement
- L.2.7.2** Test

Annex M (informative) Typical pressure regulators and pressure regulator parts

Page count: 62