

# DIN 94678:2022-12 (E)

## Devices for heat recovery from shower wastewater (DWHRD)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		4
Introduction .....		5
1 Scope .....		6
2 Normative references .....		6
3 Terms and definitions.....		7
4 Symbols and abbreviated terms.....		7
5 Requirements .....		9
5.1 Heat exchanger .....		9
5.2 Materials .....		9
5.3 Leakage display.....		9
5.4 Product families.....		10
6 Tests .....		10
6.1 Initial test.....		10
6.1.1 Volume.....		10
6.1.2 Hygiene.....		10
6.1.3 Thermal cycling .....		13
6.1.4 Leak tightness.....		15
6.1.5 Leakage display.....		15
6.1.6 Pressure resistance .....		15
6.1.7 Prior tests .....		15
6.2 Leak testing during production .....		15
7 Calculation of values for assessment of the combination of water heater and DWHRD .....		15
8 Marking .....		17
9 Technical documents .....		17
9.1 General .....		17
9.2 Installation and maintenance instructions.....		18
9.3 Operating instructions .....		18
Annex A (normative) Measurements .....		19
A.1 Temperature measurement .....		19
A.2 Volume flow rate measurement.....		20
A.3 Efficiency measurement.....		21
A.4 Pressure loss measurement.....		21
A.5 Location of the drilled hole for the leak test .....		21
Annex B (informative) Connection variants of the DWHRD .....		23
Bibliography .....		25

## Figures

Figure 1 — Assignment of symbols and schematic representation of the DWHRD using the example of the connection to the mixer taps of the shower and potable water heater (balanced connection) .....	9
Figure 2 — Example of a test set-up for hygiene testing .....	11
Figure 3 — Inflow section for DWHRD without integrated siphon.....	11

Figure 4 — Representation of the procedure for test condition 1 .....	12
Figure 5 — Representation of the procedure for test condition 2 .....	13
Figure 6 — Test procedure for thermal cycling test.....	14
Figure 7 — Graphical representation of the test criterion steady-state efficiency .....	14
Figure A.1 — Example design for a measuring sensor for temperature measurement.....	20
Figure A.2 — Drilled hole for a heat exchanger with an enclosed primary side, e.g. shower pipe .....	21
Figure A.3 — Drilled hole for a heat exchanger with an open primary side, e.g. shower drain channel.....	22
Figure B.1 — Connection of the DWHRD to the mixer taps of the shower and potable water heater (balanced connection, schematic diagram A).....	23
Figure B.2 — Connection of the DWHRD to the mixer taps of the shower (schematic diagram B) .....	24
Figure B.3 — Connection of the DWHRD to the potable water heater (schematic diagram C) .....	24

## Tables

Table 1 — Symbols and abbreviated terms.....	8
Table 2 — Test criteria for selection of the most relevant product as a representative of its product family .....	10
Table 3 — $q_{V,tp}$ depending on the load profile .....	16
Table 4 — Statement of the efficiency .....	17
Table 5 — Statement of the efficiency .....	18
Table 6 — $\eta_{DWHRD}$ depending on the load profile .....	18