

# DIN EN 17690-1:2026-02 (E)

## Components for BAC control loop - Sensors - Part 1: Room temperature sensors

---

<b>Contents</b>		<b>Page</b>
European foreword .....		4
Introduction .....		5
1	Scope .....	6
2	Normative references .....	6
3	Terms and definitions .....	6
4	Symbols, units, subscripts and abbreviations .....	8
5	Room temperature sensor device .....	9
6	Requirements .....	10
6.1	Electrical requirements .....	10
6.1.1	Electromagnetic compatibility .....	10
6.1.2	Degree of protection .....	10
6.2	Declarations by the manufacturer .....	10
6.2.1	General .....	10
6.2.2	Protection class .....	10
6.2.3	Measuring range .....	10
6.2.4	Sensor (device) accuracy .....	10
6.2.5	Time constant $t_{63}$ .....	11
6.2.6	Wall coupling coefficient $k_W$ .....	11
6.2.7	Self-heating compensation .....	12
6.2.8	Output signals .....	12
6.2.9	Power supply .....	13
6.2.10	Power consumption of the device .....	13
6.2.11	Electrical connection .....	13
6.2.12	Dimensions .....	13
6.2.13	Weight .....	13
6.2.14	Environmental conditions .....	13
7	Test set-up .....	13
7.1	Test equipment .....	13
7.1.1	Climatic chamber .....	13
7.1.2	Wall modules .....	15
7.2	Test installation .....	19
7.2.1	Mounting of the Device Under Test (DUT) .....	19
7.2.2	Wiring of the room sensor devices .....	19
7.2.3	Reference sensor position .....	19
7.3	Temperature homogeneity .....	21
7.4	Determination of the mean air velocity .....	22
7.5	Homogeneity of air velocity .....	22
8	Test methods .....	23
8.1	Sensor accuracy .....	23
8.1.1	General .....	23
8.1.2	Test conditions sensor accuracy test .....	23
8.1.3	Impact of temperature variation $t_{var}$ .....	24
8.1.4	Impact of air velocity variation $air_{vel}$ .....	24

8.1.5	Impact of power supply of the device psup .....	25
8.2	Time constant .....	25
8.2.1	General .....	25
8.2.2	Test conditions .....	26
8.3	Wall coupling .....	27
8.3.1	General .....	27
8.3.2	Test conditions .....	28
8.4	Power consumption measurement .....	29
8.4.1	General .....	29
8.4.2	Average active power .....	29
8.4.3	Average apparent power .....	30
8.4.4	Inrush peak current and periodic peak current measurement .....	30
9	Marking and documentation .....	30
9.1	Marking .....	30
9.2	Documentation .....	31
Annex A (informative) Measurements .....		32
A.1	24 V power supply / 0 V to 10 V sensor output .....	32
A.2	24 V power supply / 4 mA to 20 mA sensor output .....	33
A.3	24 V power supply (4 mA to 20 mA in the loop), 4 mA to 20 mA sensor output .....	34
A.4	24 V power supply, sensor output: Bus signal (e.g. KNX) .....	35
A.5	24 V power supply: bus powered, sensor output: Bus signal (e.g. KNX) .....	36
A.6	Inrush and periodic peak current measurement .....	36
A.7	Correction factor air velocity inside the test chamber .....	37
Bibliography .....		41