

ISO 23551-11:2024-11 (E)

Safety and control devices for gas burners and gas-burning appliances - Particular requirements - Part 11: Automatic and semi-automatic shut-off valves for operating pressure of above 500 kPa up to and including 6 300 kPa

| Contents | | Page |
|--------------------|---------------------------------------------------------------------------------|-------------|
| Foreword | | vi |
| Introduction | | vii |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Classification | 3 |
| 4.1 | Classes of controls | 3 |
| 4.1.1 | Classification based on sealing force | 3 |
| 4.1.2 | Classifications based on pressure surge | 3 |
| 4.1.3 | Classification with neither sealing force nor pressure surge | 3 |
| 4.1.4 | Classification of flow control valves for general purpose | 3 |
| 4.2 | Groups of controls | 3 |
| 4.3 | Types of DC supplied controls | 3 |
| 4.4 | Classes of control function | 3 |
| 5 | Test conditions and tolerances | 4 |
| 5.1 | Test conditions | 4 |
| 5.2 | Tolerances | 4 |
| 6 | Construction | 4 |
| 6.1 | General | 4 |
| 6.2 | Construction requirements | 6 |
| 6.2.1 | Appearance | 6 |
| 6.2.2 | Holes | 6 |
| 6.2.3 | Breather holes | 6 |
| 6.2.4 | Vent limiter | 6 |
| 6.2.5 | Screwed fastenings | 6 |
| 6.2.6 | Moving parts | 7 |
| 6.2.7 | Sealing caps | 7 |
| 6.2.8 | Disassembling and assembling for servicing and/or adjustment for controls | 7 |
| 6.2.9 | Auxiliary channels and orifices | 8 |
| 6.2.10 | Pre-setting device | 8 |
| 6.2.11 | Closed position indication | 8 |
| 6.2.12 | Specific construction | 10 |
| 6.2.13 | Flow rates of valves with modulating control | 10 |
| 6.2.14 | Bypass | 10 |
| 6.2.15 | Semi-automatic shut-off valve | 10 |
| 6.2.16 | Other controls assembled to a valve | 11 |
| 6.2.17 | Balanced valves | 11 |
| 6.3 | Materials | 11 |
| 6.3.1 | General material requirements | 11 |
| 6.3.2 | Housing | 12 |
| 6.3.3 | Springs providing closing force and sealing force | 13 |
| 6.3.4 | Resistance to corrosion and surface protection | 14 |

| | | |
|--------|-------------------------------------------------------------------|----|
| 6.3.5 | Impregnation | 14 |
| 6.3.6 | Seals for glands for moving parts | 14 |
| 6.3.7 | Jointing | 14 |
| 6.3.8 | Closure members | 14 |
| 6.3.9 | Parts transmitting the closing force | 14 |
| 6.3.10 | Balanced valves | 14 |
| 6.3.11 | Bellows | 15 |
| 6.3.12 | Hydrostatic withstand pressure test | 15 |
| 6.4 | Connections | 16 |
| 6.4.1 | General | 16 |
| 6.4.2 | Connection sizes | 16 |
| 6.4.3 | Connections types | 16 |
| 6.4.4 | Threads | 16 |
| 6.4.5 | Union joints | 16 |
| 6.4.6 | Flanges | 17 |
| 6.4.7 | Compression fittings | 17 |
| 6.4.8 | Flare connections | 17 |
| 6.4.9 | Nipples for pressure tests | 17 |
| 6.4.10 | Strainers | 18 |
| 6.4.11 | Gas connections by GQC | 18 |
| 6.4.12 | Welded connections | 18 |
| 6.5 | Gas controls employing electrical components in the gas way | 18 |
| 6.6 | Pneumatic and hydraulic actuating mechanisms | 18 |
| 7 | Performance | 19 |
| 7.1 | General | 19 |
| 7.2 | Leak-tightness | 20 |
| 7.2.1 | General | 20 |
| 7.2.2 | Requirements | 20 |
| 7.2.3 | Test | 21 |
| 7.2.4 | Pressure surge test | 22 |
| 7.3 | Torsion and bending | 22 |
| 7.3.1 | General | 22 |
| 7.3.2 | Torsion | 22 |
| 7.3.3 | Bending moment | 22 |
| 7.3.4 | Torsion and bending tests | 22 |
| 7.4 | Rated flow rate | 23 |
| 7.4.1 | General | 23 |
| 7.4.2 | Requirements | 23 |
| 7.4.3 | Test | 23 |
| 7.5 | Durability | 23 |
| 7.6 | Functional requirements | 23 |
| 7.6.1 | Closing function | 24 |
| 7.6.2 | Closing force | 24 |
| 7.6.3 | Delay time and opening time | 25 |
| 7.6.4 | Closing time | 25 |
| 7.6.5 | Sealing force | 26 |
| 7.7 | Endurance | 27 |
| 7.7.1 | Requirement | 27 |
| 7.7.2 | Test | 28 |
| 7.8 | Vibration | 30 |
| 8 | Electrical requirements | 30 |
| 8.1 | General | 30 |
| 8.2 | Requirements | 30 |
| 8.3 | Test | 30 |
| 8.4 | Protection by enclosure | 30 |
| 8.5 | Electrical components | 31 |
| 8.5.1 | Switches | 31 |
| 8.5.2 | Plug connector | 31 |
| 8.5.3 | Power saving circuit | 31 |

| | | |
|-------------|---------------------------------------------------------------------------------------------------------------------|-----------|
| 9 | Electromagnetic compatibility (EMC) | 32 |
| 9.1 | Protection against environmental influences | 32 |
| 9.2 | Harmonics and interharmonics including mains signalling at a.c. power port, low frequency immunity | 32 |
| 9.3 | Voltage dips, voltage interruptions and voltage variations in the power supply network ... | 32 |
| 9.4 | Test of influence of voltage unbalance | 32 |
| 9.5 | Surge immunity tests | 32 |
| 9.6 | Electrical fast transient/burst | 32 |
| 9.7 | Ring wave immunity | 32 |
| 9.8 | Electrostatic discharge | 33 |
| 9.9 | Radio-frequency electromagnetic field immunity | 33 |
| 9.10 | Influence of supply frequency variations | 33 |
| 9.11 | Power frequency magnetic field immunity | 33 |
| 9.12 | Evaluation of compliance | 33 |
| 10 | Marking, installation and operating instructions | 33 |
| 10.1 | Marking | 33 |
| 10.2 | Installation and operating instructions | 33 |
| 10.3 | Warning notice | 34 |
| 10.4 | Annexes | 34 |
| | Annex A (normative) Specific regional requirements in European countries | 35 |
| | Annex B (normative) Specific regional requirements in Canada and USA | 36 |
| | Annex C (normative) Specific regional requirements in Japan | 37 |
| | Annex D (normative) Specific regional requirements in China | 38 |
| | Bibliography | 39 |